




**Surface Mount LED
Right Angle Type Package**



597-2xx1-4xx

1




Dimensions in mm [inches]

PART NO.*

- 597-2002-4xx
- 597-2111-4xx
- 597-2201-4xx
- 597-2212-4xx
- 597-2222-4xx
- 597-2311-4xx
- 597-2401-4xx

COLOR

- Red
- Red
- Orange
- Orange
- Green
- Green
- Yellow



*ORDERING INFORMATION	
597-2xx1-4xx	
packaging option	
02	20 pieces on tape
07	7" reel, 3000 pcs/reel

Features

- Compatible with automatic placement equipment
- Compatible with infrared reflow processes
- Packaged on 8mm tape, 7" reels (meets EIA-481-1 standard)
- Helps to eliminate mixed technology PC board processing

ABSOLUTE MAXIMUM RATINGS (T _A =25°C)	Red	Red	Orange	Orange	Amber	Green	Yellow
	-2202	-2111	-2201	-2212	-2222	-2311	-2401
Power Dissipation (mW)	81	57.5	70	81	81	70	70
Forward Current (mA)	25	25	25	25	25	25	25
Derating (mA/°C) Above 25°C	.43	.36	.36	.43	.43	.36	.36
Peak Current (mA)	30	60	60	30	30	60	60
Pulse width = 100 μs	100*			100	100		
Operating Temperature (°C)	-40/+85	-30/+85	-30/+85	-40/+85	-40/+85	-30/+85	-30/+85
Storage Temperature (°C)	-40/+100	-40/+100	-40/+100	-40/+100	-40/+100	-40/+100	-40/+100
Soldering Temperature	260°C, 5 seconds max						
<i>Solder Adherence per MIL-STD-202E, Method 208C</i>							
OPERATING CHARACTERISTICS (T _A =25°C)	Red	Red	Orange	Orange	Amber	Green	Yellow
	-2202	-2111	-2201	-2212	-2222	-2311	-2401
Luminous Intensity (mcd)	Min.	16	6.2	1.5	16	16	2.6
	Typical	50	12.4	3	65	65	5.2
I _F =20mA							
Peak Wavelength (nm)	Typical	630	660	605	609	592	580
λ _{Peak}							
Viewing Angle (2Θ 1/2)	Typical	130°	130°	130°	130°	130°	130°
Forward Voltage (V)	Typical	1.9	1.7	2.2	1.9	1.9	2.1
	Max.	2.4	2.3	2.8	2.4	2.4	2.8
I _F =20mA							
Reverse Current (μA)	Max	100*	100	100	100	100*	100
(V _R = 4V) * (V _R = 5V)							

Θ 1/2 is the off axis angle at which the luminous intensity is half the axial luminous intensity

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Dialight:

[597-2201-407](#) [597-2111-407](#) [597-2311-407](#) [597-2401-407F](#) [597-2401-407](#) [597-2111-402F](#) [597-2401-402F](#) [597-2311-402F](#) [597-2311-402F](#)