

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0705530044

Status:

Active

Overview:

SL Modular Connectors

Description:

2.54mm Pitch SL Header, Low Profile, Single Row, Right Angle, 3.05mm Pocket, Shrouded, 10 Circuits, Tin (Sn) Plating



Series image - Reference only

- Documents:
- 3D Model

Drawing (PDF)

Product Specification PS-70400-001 (PDF)

Product Specification PS-70541-001 (PDF)

Product Specification TS-70541-001-001 (PDF)

Product Specification TS-70541-100-001 (PDF)

Packaging Specification PK-70873-0015 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification		
CSA	LR19980	
UL	E29179	
General		
Product Family	PCB Headers	
Series	70553	
Application	Signal, Wire-to-Board	
Overview	SL Modular Connectors	
Product Name	SL	
UPC	800753764347	
Physical		
Breakaway	No	
Circuits (Loaded)	10	
Circuits (maximum)	10	
Color - Resin	Black	
Durability (mating cycles max)	25	
Flammability	94V-0	
Glow-Wire Capable	No	
Guide to Mating Part	Yes	
Lock to Mating Part	Yes	
Material - Metal	Brass, Phosphor Bronze	
Material - Plating Mating	Tin	
Material - Plating Termination	Tin	
Material - Resin	High Temperature Thermoplastic	
Net Weight	2.097/g	
Number of Rows	1	
Orientation	Right Angle	
PC Tail Length	3.30mm	
PCB Locator	No	
PCB Retention	None	
PCB Thickness - Recommended	1.60mm	
Packaging Type	Tube	
Pitch - Mating Interface	2.54mm	
Plating min - Mating	3.810µm	
Plating min - Termination	3.810µm	
Polarized to Mating Part	Yes	
Shrouded	Fully	
Stackable	No	
Temperature Range - Operating	-40° to +105°C	
Termination Interface: Style	Through Hole	
Electrical		
Current - Maximum per Contact	3.0A	

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per -
ED/61/2018 (27 June
2018)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

Green Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series

70553 Series

Mates With

SL Crimp Housing [70066](#) Option N, [70066](#)
Option G, [70430](#) Option G, [70400](#) Option G

Voltage - Maximum	250V
Solder Process Data	
Lead-freeProcess Capability	WAVE
Material Info	
Reference - Drawing Numbers	
Packaging Specification	PK-70873-0015
Product Specification	PS-70400-001, PS-70541-001, TS-70541-001-001, TS-70541-100-001
Sales Drawing	SDA-70553-****

This document was generated on 11/05/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[70553-0044](#)