

Relay base - PR1-BSP3/2X21 - 2833534

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Relay base PR1..., for miniature power relay or miniature switching relay with 1 or 2 PDT or solid-state relay of same construction, 1/3 level design, spring-cage connections, connection facility for input/interference suppression modules




Your advantages

- Relay base family that can be fitted with 1 PDT or 2 PDT relays or solid-state relays
- Relay retaining bracket with labeling field and ejection function
- Plug-in input/interference suppression modules



Key Commercial Data

Packing unit	10 pc
GTIN	 4 017918 933784
GTIN	4017918933784

Technical data

Dimensions

Width	16 mm
Height	97 mm
Depth with retaining bracket	72 mm (EL1-P16)
	80 mm (EL1-P25)

Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C
---------------------------------	------------------

Connection data, output side

Connection name	Output side
Connection method	Spring-cage connection
Stripping length	10 mm
Conductor cross section solid	0.5 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.5 mm ² ... 1.5 mm ²

Relay base - PR1-BSP3/2X21 - 2833534

Technical data

Connection data, output side

Conductor cross section AWG	26 ... 16
-----------------------------	-----------

General

Nominal voltage U _N	300 V AC/DC
Nominal current I _N	10 A
Mounting position	any

Standards and Regulations

Connection in acc. with standard	CSA
----------------------------------	-----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

CSA		http://www.csagroup.org/services-industries/product-listing/	255476
-----	--	---	--------

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
---------------	--	---	---------------

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
----------------	--	---	---------------

EAC			RU C- DE.A*30.B.01082
-----	--	--	--------------------------

Relay base - PR1-BSP3/2X21 - 2833534

Approvals

cULus Recognized



Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2833534](#)