

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

ALL RIGHTS RESERVED.

LOC J DIST ZDI

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B1		REVISED PER ECO-11-005030	24MAR11	RK	HMR
C		REVISE PER ECR-14-001819	11FEB14	E.C	H.M

NOTES

1. MATERIAL: HOUSING: GLASS FILLED THERMO PLASTIC, POLYESTER(94V-0), COLOR: BLACK
 TAB CONTACT: COPPER ALLOY
 RETENTION LEG: BRASS
 △ FINISH (CONTACT AREA): 0.38μm MIN GOLD PLATING OVER Ni PLATING
 △ FINISH (RETENTION LEG): TIN PLATED (CONTACT TAIL) OVER NICKEL

RECOMENDED PC BOARD HOLE PATTERN (TOL: ±0.05)
 PC BOARD THICKNESS: 1.6 ± 0.3
 注記 (CONNECTOR MOUNT SIDE)

1. 材料: ハウジング: ガラス入り熱可塑性ポリエステル樹脂 (94V-0), 色: 黒
 ポリエステル樹脂 (94V-0), 色: 黒
 タブ コンタクト: 銅合金
 リテンション レグ: 黄銅
 △ めっき: コンタクト: 全面Ni下地 接触部: 0.38μm MIN金めっき
 △ めっき: リテンションレグとコンタクト半田付部: ニッケル下地の上にスズめっき

DIMENSIONS: 単位 種 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 一般公差 1% : ±0.3 3% : >10 : ±0.35 10% : >30 : ±0.4 ANGLE : ±3°	DWN K.IKEDA 24/FEB/'00	NAME 2列 ヘッダーアセンブリー 20P (水平タイプ) DOUBLE ROW HEADER ASS'Y 20P ("H" TYPE) <DYNAMIC D-2100D>	SIZE A3	CAGE CODE 00779	DRAWING NO C-1376137	RESTRICTED TO -	
		CHK Y.KATO 28/FEB/'00						APVD I.HASEGAWA 28/FEB/'00
MATERIAL 注記参照 SEE NOTES	FINISH 注記参照 SEE NOTES	PRODUCT SPEC 108-5619	APPLICATION SPEC 114-5258	WEIGHT 71	CUSTOMER DRAWING			

(CUSTOMER DRAWING) 顧客用図面

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1376137-2](#)