

## Fuse plug - ST-SILED 12-UK 4 - 0921024

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, Nominal current: 6.3 A, Length: 33.1 mm, Width: 6.1 mm, Height: 45.7 mm, Color: black

The illustration shows the version without LED/light indicator



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 010287
Weight per Piece (excluding packing)	5.88 g
Custom tariff number	85363010
Country of origin	Poland

### Technical data

#### General

Note	If the fuse is defective, the downstream circuit is not off load
Color	black
Insulating material	PA
Flammability rating according to UL 94	V2

#### Dimensions

Width	6.1 mm
Length	33.1 mm

#### General

Fuse	G / 5 x 20
Insulating material group	CTI 600
Maximum load current	6.3 A

# Fuse plug - ST-SILED 12-UK 4 - 0921024

## Technical data

### General

Nominal current $I_N$	6.3 A
Nominal voltage $U_N$	250 V

### Connection data

Connection method	Plug connection
-------------------	-----------------

### Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

## Classifications

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27142001

### ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC000036

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

---

# Fuse plug - ST-SILED 12-UK 4 - 0921024

## Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized

---


Ex Approvals


---


Approvals submitted

---


## Approval details

CSA 	
Nominal current I <sub>N</sub>	10 A
Nominal voltage U <sub>N</sub>	300 V

UL Recognized 	
Nominal current I <sub>N</sub>	6.3 A
Nominal voltage U <sub>N</sub>	300 V

cUL Recognized 	
Nominal current I <sub>N</sub>	6.3 A
Nominal voltage U <sub>N</sub>	300 V

EAC
-----

cULus Recognized 
--

## Fuse plug - ST-SILED 12-UK 4 - 0921024

Accessories

Accessories

Documentation

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[0921024](#)