


## PCB terminal block - MK3DS 1,5/ 3-5,08-BC GY - 1747672

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, nominal current: 15 A, pitch: 5.08 mm, number of positions: 3, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: gray



### Key Commercial Data

|              |                                                                                                       |
|--------------|-------------------------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                                 |
| GTIN         | <br>4 046356 298629 |
| GTIN         | 4046356298629                                                                                         |

### Technical data

#### Item properties

|                       |                |
|-----------------------|----------------|
| Number of positions   | 3              |
| Drive form screw head | Slotted (L)    |
| Screw thread          | M3             |
| Pin layout            | Linear pinning |

#### Dimensions for the product

|                             |          |
|-----------------------------|----------|
| Length [ l ]                | 32.25 mm |
| Width [ w ]                 | 17.78 mm |
| Height [ h ]                | 36.6 mm  |
| Pitch                       | 5.08 mm  |
| Height (without solder pin) | 37 mm    |
| Solder pin [P]              | 3.5 mm   |
| Dimension a                 | 10.16 mm |

#### Dimensions for PCB design

|               |        |
|---------------|--------|
| Hole diameter | 1.3 mm |
|---------------|--------|

#### Packaging information

|                            |                     |
|----------------------------|---------------------|
| Type of packaging          | packed in cardboard |
| Pieces per package         | 50                  |
| Denomination packing units | Pcs.                |

#### Air clearances and creepage distances

|         |       |
|---------|-------|
| Voltage | 250 V |
|---------|-------|

# PCB terminal block - MK3DS 1,5/ 3-5,08-BC GY - 1747672

## Technical data

### Standards and Regulations

|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
|                                        | CUL    |
| Flammability rating according to UL 94 | V0     |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

#### Approvals

UL Recognized / cUL Recognized / IEC CB Scheme / SEV / EAC / cULus Recognized

#### Ex Approvals

### Approval details

|                                                                                                                                                                                                                                                                      |       |       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|
| UL Recognized  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> FILE E 60425 |       |       |
|                                                                                                                                                                                                                                                                      | D     | B     |
| Nominal voltage UN                                                                                                                                                                                                                                                   | 300 V | 125 V |
| Nominal current IN                                                                                                                                                                                                                                                   | 10 A  | 10 A  |
| mm²/AWG/kcmil                                                                                                                                                                                                                                                        | 30-14 | 30-14 |

|                                                                                                                                                                                                                                                                       |       |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|
| cUL Recognized  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> FILE E 60425 |       |       |
|                                                                                                                                                                                                                                                                       | D     | B     |
| Nominal voltage UN                                                                                                                                                                                                                                                    | 300 V | 125 V |
| Nominal current IN                                                                                                                                                                                                                                                    | 10 A  | 10 A  |
| mm²/AWG/kcmil                                                                                                                                                                                                                                                         | 30-14 | 30-14 |

## PCB terminal block - MK3DS 1,5/ 3-5,08-BC GY - 1747672

### Approvals

|                    |                                                                                   |                                                           |         |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------|---------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | CH-8225 |
| Nominal voltage UN | 250 V                                                                             |                                                           |         |
| Nominal current IN | 17.5 A                                                                            |                                                           |         |
| mm²/AWG/kcmil      | 2.5                                                                               |                                                           |         |

|                    |                                                                                   |                                                                                                                                                     |            |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| SEV                |  | <a href="https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html">https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html</a> | IK-3542-M1 |
| Nominal voltage UN | 250 V                                                                             |                                                                                                                                                     |            |
| Nominal current IN | 17.5 A                                                                            |                                                                                                                                                     |            |
| mm²/AWG/kcmil      | 2.5                                                                               |                                                                                                                                                     |            |

|     |                                                                                     |         |  |
|-----|-------------------------------------------------------------------------------------|---------|--|
| EAC |  | B.01742 |  |
|-----|-------------------------------------------------------------------------------------|---------|--|

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| cULus Recognized |  |
|------------------|-------------------------------------------------------------------------------------|

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

1747672