

## 3-Termal 500mA Negative Voltage Regulator

### DESCRIPTION


The TS79M00 series of fixed output negative voltage regulators are intended as complements to the popular TS78M00 series device. These negative regulators are available in the same seven-voltage options as the TS7900 devices. In addition, one extra voltage option commonly employed in MECL systems is also available in the negative TS79M00 Series. Available in fixed output voltage options from -5.0 and -12 volts, these regulators employ current limiting, thermal shutdown, and safe-area compensation--making them remarkably rugged under most operating conditions. With adequate heat sinking they can deliver output currents in excess of 0.5 ampere.

### FEATURES

- Output Voltage: -5 & -12V
- Output current up to 0.5A
- No external components required
- Internal thermal overload protection
- Internal short-circuit current limiting
- Output transistor safe-area compensation
- Output voltage offered in 4% tolerance
- Compliant to RoHS Directive 2011/65/EU and WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

### APPLICATION

- Switching power supply
- Home appliance




#### Pin Definition:

1. Ground
2. Input (tab)
3. Output

**Notes:** MSL 3 (Moisture Sensitivity Level) per J-STD-020

### TYPICAL APPLICATION CIRCUIT



A common ground is required between the input and the output voltages. The input voltage must remain typically 2V above the output voltage even during the low point on the Input ripple voltage.

XX = these two digits of the type number indicate voltage.

\* =  $C_{IN}$  is required if regulator is located an appreciable distance from power supply filter.

\*\* =  $C_{OUT}$  is not needed for stability; however, it does improve transient response.

**ABSOLUTE MAXIMUM RATINGS**

PARAMETER	SYMBOL	LIMIT	UNIT
Input Voltage	$V_{IN}$	-35	V
Power Dissipation	$P_D$	Internal Limited	W
Operating Junction Temperature	$T_J$	0~+125	°C
Storage Temperature Range	$T_{STG}$	-65~+150	°C

**THERMAL PERFORMANCE**

PARAMETER	SYMBOL	LIMIT		UNIT
		TO-220	TO-252	
Junction to Case Thermal Resistance	$R_{\theta JC}$	5	6	°C/W
Junction to Ambient Thermal Resistance	$R_{\theta JA}$	65	92	°C/W

**Notes:**  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistances. The case thermal reference is defined at the solder mounting surface of the drain pins.  $R_{\theta JA}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.  $R_{\theta JA}$  shown below for single device operation on FR-4 PCB in still air.

**ELECTRICAL SPECIFICATIONS TS79M05**

( $V_{IN}=-10V$ ,  $I_{OUT}=350mA$ ,  $0^{\circ}C \leq T_J \leq 125^{\circ}C$ ,  $C_{IN}=0.33\mu F$ ,  $C_{OUT}=0.1\mu F$ , unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	$T_J=25^{\circ}C$	$V_{OUT}$	-4.80	-5	-5.20	V
	$-7.5V \leq V_{IN} \leq -20V$ , $5mA \leq I_{OUT} \leq 500mA$ , $P_D \leq 5W$		-4.75	-5	-5.25	
Line Regulation	$T_J=25^{\circ}C$	$REG_{LINE}$	--	7	50	mV
			--	2	30	
Load Regulation	$T_J=25^{\circ}C$	$REG_{LOAD}$	--	20	100	
			--	10	50	
Quiescent Current	$I_{OUT}=0$ , $T_J=25^{\circ}C$	$I_Q$	--	4	8	mA
Quiescent Current Change	$-7.5V \leq V_{IN} \leq -25V$	$\Delta I_Q$	--	--	1	
	$5mA \leq I_{OUT} \leq 500mA$		--	--	0.5	
Output Noise Voltage	$10Hz \leq f \leq 100kHz$ , $T_J=25^{\circ}C$	$V_N$	--	40	--	$\mu V$
Ripple Rejection Ratio	$f=120Hz$ , $-8V \leq V_{IN} \leq -18V$	RR	54	66	--	dB
Voltage Drop	$I_{OUT}=500mA$ , $T_J=25^{\circ}C$	$V_{DROP}$	--	2	--	V
Peak Output Current	$T_J=25^{\circ}C$	$I_{O\ peak}$	--	2.1	--	A
Temperature Coefficient of Output Voltage	$I_{OUT}=5mA$ , $0^{\circ}C \leq T_J \leq 125^{\circ}C$	$\Delta V_{OUT} / \Delta T_J$	--	-0.1	--	mV/°C

**ELECTRICAL SPECIFICATIONS TS79M12**

 ( $V_{IN} = -19V$ ,  $I_{OUT} = 350mA$ ,  $0^{\circ}C \leq T_J \leq 125^{\circ}C$ ,  $C_{IN} = 0.33\mu F$ ,  $C_{OUT} = 0.1\mu F$ , unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	$T_J = 25^{\circ}C$	$V_{OUT}$	-11.53	-12	-12.48	V
	$-14.5V \leq V_{IN} \leq -27V$ , $5mA \leq I_{OUT} \leq 500mA$ , $P_D \leq 5W$		-11.42	-12	-12.60	
Line Regulation	$T_J = 25^{\circ}C$	$REG_{LINE}$	--	10	240	mV
	$-14.5V \leq V_{IN} \leq -30V$		--	3	120	
Load Regulation	$T_J = 25^{\circ}C$	$REG_{LOAD}$	--	12	240	
	$5mA \leq I_{OUT} \leq 500mA$		--	4	120	
Quiescent Current	$I_{OUT} = 0$ , $T_J = 25^{\circ}C$	$I_Q$	--	4.3	8	mA
Quiescent Current Change	$-14.5V \leq V_{IN} \leq -30V$	$\Delta I_Q$	--	--	1	
	$5mA \leq I_{OUT} \leq 500mA$		--	--	0.5	
Output Noise Voltage	$10Hz \leq f \leq 100kHz$ , $T_J = 25^{\circ}C$	$V_N$	--	75	--	$\mu V$
Ripple Rejection Ratio	$f = 120Hz$ , $-15V \leq V_{IN} \leq -25V$	RR	55	70	--	dB
Voltage Drop	$I_{OUT} = 500mA$ , $T_J = 25^{\circ}C$	$V_{DROP}$	--	2	--	V
Peak Output Current	$T_J = 25^{\circ}C$	$I_{O \text{ peak}}$	--	2.1	--	A
Temperature Coefficient of Output Voltage	$I_{OUT} = 5mA$ , $0^{\circ}C \leq T_J \leq 125^{\circ}C$	$\Delta V_{OUT} / \Delta T_J$	--	-1	--	mV/ $^{\circ}C$


**Note:**

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.


**ORDERING INFORMATION**

OUTPUT VOLTAGE	PART NO.	PACKAGE	PACKING
5V	TS79M05CZ C0G	TO-220	50pcs / Tube
	TS79M05CP ROG	TO-252	2,500pcs / 13" Reel
12V	TS79M12CP ROG	TO-252	2,500pcs / 13" Reel


## CHARACTERISTICS CURVES




**Figure 1. Worst Case Power Dissipation vs. Ambient Temperature (TO-220)**




**Figure 2. Peak Output Current as a Function of Input-Output Differential Voltage**




**Figure 3. Bias Current vs. Input Voltage**



**Figure 4. Bias Current vs. Output Current**




**Figure 5. Ripple Rejection vs. Frequency**



**Figure 6. Ripple Rejection vs. Output Voltage**


## APPLICATION INFORMATION




**Figure 7. DPAK Thermal Resistance and Maximum Power Dissipation vs. P.C.B Copper Length**

**PACKAGE OUTLINE DIMENSIONS** (Unit: Millimeters)

**TO-220**



**MARKING DIAGRAM**



**XX** = Output Voltage

**05** = -5V

**Y** = Year Code

**M** = Month Code for Halogen Free Product

**O** =Jan **P** =Feb **Q** =Mar **R** =Apr

**S** =May **T** =Jun **U** =Jul **V** =Aug


**W** =Sep **X** =Oct **Y** =Nov **Z** =Dec

**L** = Lot Code


**CZ** = Package code

**PACKAGE OUTLINE DIMENSIONS** (Unit: Millimeters)


**TO-252 (DPAK)**



**SUGGESTED PAD LAYOUT** (Unit: Millimeters)



**MARKING DIAGRAM**



**XX** = Output Voltage

**05** = -5V **12** = -12V

**Y** = Year Code

**M** = Month Code for Halogen Free Product

**O** = Jan **P** = Feb **Q** = Mar **R** = Apr

**S** = May **T** = Jun **U** = Jul **V** = Aug

**W** = Sep **X** = Oct **Y** = Nov **Z** = Dec

**L** = Lot Code

**CP** = Package code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Taiwan Semiconductor:

[TS79M05CZ](#) [TS79M05CP](#) [TS79M15CP](#) [TS79M15CZ](#) [TS79M09CZ](#) [TS79M09CP](#) [TS79M12CP](#) [TS79M08CZ](#)  
[TS79M08CP](#) [TS79M06CZ](#) [TS79M06CP](#) [TS79M24CP](#) [TS79M24CZ](#) [TS79M18CZ](#) [TS79M18CP](#) [TS79M05CZ C0G](#)  
[TS79M05CP ROG](#) [TS79M12CP ROG](#)