

Plastic label - UC-EMLP (20X8) YE - 0822631

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Plastic label, Sheet, yellow, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: Adhesive, Lettering field: 20 mm x 8 mm

Product Features

- The UC-EMLP ... UniCard labeling range includes self-adhesive device markers with good adhesive properties
- The markers, which are supplied in uniform sheets, can be labeled quickly and easily using the BLUEMARK LED
- The wide temperature range means that the labels can be used in control cabinets as well as the field
- The sheets provide space for including function texts
- The format automatically ensures printing with a high degree of positioning accuracy



Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|----------|
| Minimum order quantity | 10 pc |
| Weight per Piece (excluding packing) | 6.88 g |
| Custom tariff number | 39269097 |
| Country of origin | Poland |

Technical data

Dimensions

| Length (b) | 20 mm |
|------------|-------|
| Width (a) | 8 mm |

Ambient conditions

| Ambient temperature (operation) | -40 °C 120 °C |
|---------------------------------|---------------|
|---------------------------------|---------------|

General

| Color | yellow |
|--|--------------------------------|
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | V2 |

04/13/2016 Page 1 / 3



Plastic label - UC-EMLP (20X8) YE - 0822631

Technical data

General

| Material | PA |
|-------------------------------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 10 |
| Number of individual labels per row | 2 |
| Marking mounting type | Adhesive |

Standards and Regulations

| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|--|-----------------------------|
| Flammability rating according to UL 94 | V2 |

Classifications

eCl@ss

| eCl@ss 4.0 | 24190208 |
|------------|----------|
| eCl@ss 4.1 | 24190208 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |

ETIM

| ETIM 2.0 | EC000761 |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

UNSPSC

| UNSPSC 6.01 | 30211811 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Accessories

Accessories

Magazine



Plastic label - UC-EMLP (20X8) YE - 0822631

Accessories

Magazine - P1 UC-MAG 6 - 5146121



Magazine, for CMS-P1-PLOTTER, for accommodating UC-EMP..., UC-EMLP...

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 0822631