

# Cable sleeve - CES-LTPG-GY-24 - 0801697

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Large, slotted cable sleeves suitable for cables with a diameter of 23 ... 24 mm, material: SEBS



### **Product Description**

Slotted sleeves for accommodating pre-assembled cables and lines with a diameter of 23 ... 24 mm, can be used in CES sealing frames. When fitted, the sleeves also ensure strain relief according to DIN EN 50262.



# Key Commercial Data

| Packing unit                         | 1 pc     |
|--------------------------------------|----------|
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 26.0 g   |
| Custom tariff number                 | 85472000 |
| Country of origin                    | Poland   |

# Technical data

#### Dimensions

| External cable diameter | 1x 23 mm 24 mm |
|-------------------------|----------------|
| Length                  | 53 mm          |
| Width                   | 39 mm          |
| Height                  | 17 mm          |

### Ambient conditions

| Degree of protection            | IP54 (for sealing frames with screw locking. IP44 sealing frames with locking latch.) |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C 80 °C (static)   |

#### General

| Product description | Slotted sleeves for accommodating pre-assembled cables and lines with a diameter of 23 24 mm, can be used in CES sealing frames. When fitted, the sleeves also ensure strain relief according to DIN EN 50262. |
|---------------------|--|
|                     | the sleeves also ensure strain relief according to DIN EN 50262.   |



# Cable sleeve - CES-LTPG-GY-24 - 0801697

# Technical data

#### General

| No. of conductors                      | 1    |
|--|------|
| Material                               | SEBS |
| Flammability rating according to UL 94 | V0   |
| Color                                  | gray |

## Standards and Regulations

| Connection in acc. with standard       | CUL |
|--|-----|
| Flammability rating according to UL 94 | V0  |

# Classifications

## eCl@ss

| eCl@ss 4.0 | 27081002 |
|------------|----------|
| eCl@ss 4.1 | 27081002 |
| eCl@ss 5.0 | 27081002 |
| eCl@ss 5.1 | 27081002 |
| eCl@ss 6.0 | 27081002 |
| eCl@ss 7.0 | 27081002 |
| eCl@ss 8.0 | 27069220 |

## ETIM

| ETIM 3.0 | EC000879 |
|----------|----------|
| ETIM 4.0 | EC000451 |
| ETIM 5.0 | EC000451 |

### UNSPSC

| UNSPSC 6.01   | 30212109 |
|---------------|----------|
| UNSPSC 7.0901 | 39121708 |
| UNSPSC 11     | 39121708 |
| UNSPSC 12.01  | 39121708 |
| UNSPSC 13.2   | 39121708 |

# Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GL / cULus Recognized



# Cable sleeve - CES-LTPG-GY-24 - 0801697

## Approvals

Ex Approvals

Approvals submitted

Approval details


UL Recognized 🔊


cUL Recognized 🔊

GL

cULus Recognized

Drawings





Dimensional drawing

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 0801697