



1 2 3 4 5 6

LOADING PATTERN MATING SIDE


f	6	6	6	6	6	6	6	6	6	6	6
e	E	E	E	E	E	E	E	E	E	E	E
d	E	E	E	E	E	E	E	E	E	E	E
c	E	E	E	E	E	E	E	E	E	E	E
b	E	E	E	E	E	E	E	E	E	E	E
a	E	E	E	E	E	E	E	E	E	E	E
z	6	6	6	6	6	6	6	6	6	6	6
P	0		0		5		1	0			
O											
S	1										

LOADED CONNECTOR ASSEMBLY
(FOR EXAMPLE)

CONTACT OVERVIEW



LAY-OUT P.C.B.-HOLE

LEAD FREE INDICATOR : LF = LEAD FREE
(DIGIT 15 & 16)

HM2P09PME12J----

PLATING CODE (DIGIT 13 AND 14)

(REF DRW NO. BS,C , 201844 , 003)

NOTES

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001
CATALOG NO: HM2P09PME12J----

mat'l. code SEE NOTE 4				surface		tolerance		projection	product family
ltr	ecn no	dr	date	tolerances unless otherwise specified		ISO 406	ISO 1302	ISO 1101	MILLIPACS
A	I06-0001	MINI	2006-01-04	angles	linear	.0±0.2		MM	title
B	I06-0141	MINI	2006-08-08			.00±0.01			
				0°±1°					MPAC5 5+2R STR HDR PF CONN TYPE C
						dr	MINI K VANDANATH	2006-01-04	dwg no
						engr	BIJU K PAUL	2006-01-04	
						chr	BIJU K PAUL	2006-08-08	
						appd	BIJU K PAUL	2006-08-08	
sheet		revision	B						sheet 1 of 1
index		sheet	1						size A3



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2P09PME12JGF](#) [HM2P09PME12JGFLF](#)