

SPECIFICATIONS

FUNCTION:
2P1T OFF-(ON), LOCK-ON

RATINGS:
ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E194579):
17A 125VAC [cUrus]
12A 250VAC [cUrus]

ELECTRICAL LIFE:
6,000 Cycles [cUrus]

TEMPERATURE:
Operating: 0°C to 65°C [cUrus]


APPROVALS:



COLORS

BODY: White
ACTUATOR: Black
LOCK: Black

SCHEMATIC



REV.	DATE	BY	CHK
A	10/09/23	BMA	CAB
B	11/09/23	BMA	CAB
B	11/09/23	BMA	CAB

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

REV.	DESCRIPTION	DATE	BY
A	2019	11/09/19	BMA
B	2019	11/09/19	BMA

INCHES [MILLIMETERS]
GENERAL TOLERANCES ±0.008 [±0.2] / ±.1
SCALE DRAWING NOT TO SCALE

HY37-6EE6-011-0211	DATE: SEPTEMBER 29, 2010
34-HY376E60110211	REVISION: B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[E-Switch:](#)

[HY37-6E6-011-0211](#)