	4		3				2				
	THIS DRAWING IS UNPUBLISHED. RELEASED FOR VERTRAULICHE UNVEROEFFENTLICHTE ZEICHNUNG FREI FUER VERO	R PUBLICATION DEFFENTLICHUNG	-,			l	_OC DIST				
	C COPYRIGHT - ⁷⁸ By - ALLE	RIGHTS RESERVED. RECHTE VORBEHALTEN					IR –	P L	rr 🛛		
						L		s	2 F	CO-10-	003194
										CR-10-	
D											
			Δ						54 E	CR-10-	026307
		Z. Z				\A_ P	eile— N N OPTIC	lr. NAL	wał BF	nlwei ROUG	ise GHT I
						Δĸ	ammer-	- N	r. \	wahlv	weise
							ammer- AVITY—				
		<u> </u>				∕_3 F M	irmenlo ANUFACI	go Ture	wa IR-	hlwe LOGC	ise) OP ⁱ
			<u>SECTION A</u>			•	efeucht				
		3	AT THE INSIDE	<u>EDGES)</u>		Μ	OISTURIZ	ZЕD	BEF	FORE	PAC
	7.4 ±0.1		1	DETENT			vorsich				
							eile zur				knen
						Z	eit vor	gei	ora	uch	
С		4 W W	<i>Y</i>				CAUTION				
				<u>ETAIL_A</u> CALE_5:1		^	NVIRONN				
		0 4 0	2			<u> </u>	BSOLETE F RENAUD/[PARTS	S: 0	BSOLE	ete ci
				+		D.	RENAUD/L).SINI	SI		
						$\overline{2}$ PC	DSSIBLE N	OLD	DET	ENTS	on t
						FR	REE POSIT	ON A	ALON	IG TH	E EDO
		Ţ			4	—	3-926 522-3	5 A	-	PA 6.6	6(V–0)
	N 522	0.45±0.2			4	—	2-926 522-	A	-	ZYTEL	L 101
	$\left \begin{array}{c} C \\ 4 \end{array} \right $					-	1-926 522-	3 S	-	PA 6.6	6(V-0)
	· · · · · · · · · · · · · · · · · · ·					_	1-926 522-	2 R	-	PA 6.6	s(v−o)
		 A				_	1-926 522-	1 S	- 1	PA 6.6	6(V-0)
В					BSOLETE	_	926 522-6	R	_		E 103
				/ / / /		_	926 522-5		_		L 101
	^				BSOLETE	_	926 522-4		_		L 101
	2				BSOLETE	_	926 522-3		_		L 101
					SOLETE	_	926 522-3	R	_		L 101
						- CUSTOMER	926 522-1 TE	R	-		L 101
		<u>}</u>				PART NO	PART NO	REV.			TERIAL
		, ,				ONTROLLED DOCU	Ju	kobeit	11-1	NOV-98 -	
				DIMENSIONS MASSE\NHEITE		TOLERANCES UNL OTHERWISE SPECI ALLGEMEINTOLERA	ESS APVD			- N4	AME
				mm		0 PLC ± 0.2	PRODUCT PRODUKTS	SPEC PEZ.			
А						1 PLC ± 0.2 2 PLC ± 0.2 3 PLC ± -		ON SPEC			
						4 PLC ± -	·,30' APPLICATI VERARBEI	TÜNĞŚŚPE	Ζ.	5	SIZE CAG
				MATERIAL		FINISH/OBERFLAECHE/F				/_	4300
				-		-		MER [DRAWI		NDENZE
	1470-19 (3/11)			1		1	L				

	REVISIONS aenderungen description		DATE	DWN	APVD				
	BESCHREIBUNG								
4			30JAN10		HMR				
5 7			28JUL10		PCH	D			
/			18JAN11	KK	HMR				
(angebra N	cht							
	e angebr BROUGHT								
	angebra TIONAL B		IN						
	verpac CKING	ken							
nicht heraus 🛆									
n umwelt für lange									
ose A parts to dry time before use									
CIS STREAMLINING PER									
	IS SIREAMI	lining pe	ĸ						
	HE INNER			λRΤ,					
	GES; SIZE	MAX 0.3m	ım.						
))	ORANGE	-			-				
1	SCHWARZ	-			-				
))	ORANGE	-			-				
))	NATUR	-			-				
))	SCHWARZ	-			-	_			
3	SCHWARZ	-			-	В			
1	BLAU	-			-				
1	GELB	-			_				
1	ROT	-			_				
1	NATUR	_			_				
1	SCHWARZ	_			_				
	SURFACE	DE	SCRIPTION		ITEM NO				
	COLOR								
ETE TE Connectivity									
2 POS.POSITIVE LOCK GEHAEUSE									
CAGE CODE DRAWING NO ZEICHNUNGS-NR. 00779 C-926522 - RESTRICTED TO NUR FUER -									
ZE	ICHNUNG		SHEET OF BLATT 1 VON 1	RE	′S4				
		, ···· <u>·</u> · · · · · · · · · · · · · · ·	1 1011						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-926522-3</u>