

Antenna - RAD-ISM-2400-ANT-PAR-19-0 - 2867885

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Parabolic antenna, IP65 degree of protection, 19 dBi gain, linear vertical, N (female) connection, impedance 50 Ω, apex angle h/v 17°/11°

Product Description

The parabolic antenna may only be used with the unidirectional transmitter and bidirectional receivers in conjunction with extension cable RAD-CAB-EF393-15m as the maximum permissible value of 20 dB for emitted power will otherwise be exceeded.

Product Features

- For large distances with a line of sight



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	3240.0 g
Custom tariff number	85177019
Country of origin	China

Technical data

Dimensions

Width	610 mm
Height	419 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

General

With connecting cable	yes
Frequency range	2.4 GHz
	2.4 GHz

Antenna - RAD-ISM-2400-ANT-PAR-19-0 - 2867885

Technical data

General

Horizontal beamwidth	17 °
Vertical beamwidth	11 °
Impedance	50 Ω
Gain	19 dBi
Connection method	N (female)
Mounting type	Mast mounting

Classifications

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	19070102
eCl@ss 5.1	19070102
eCl@ss 6.0	19070102
eCl@ss 7.0	19070102
eCl@ss 8.0	19070105
eCl@ss 9.0	19070105

ETIM

ETIM 2.0	EC000416
ETIM 3.0	EC001698
ETIM 4.0	EC001698
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706
UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2867885](#)