

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Halogen free available upon request by adding suffix "-HF"
- Fast Switching Speed
- For General Purpose Switching Applications
- Surface Mount Package Ideally Suited for Automatic Insertion
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)

Mechanical Data

- Marking Code: T5
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

Maximum Ratings @ 25° C Unless Otherwise Specified

Reverse Voltage	V _R	75	V
Peak Reverse Voltage	V _{RM}	100	V
Average Rectified Current	٩	250	mA
Peak Forward Surge Current	I _{FSM}	2	А
Power Dissipation	PD	500	mW
Thermal Resistance*	Rthja	250	°C/W
Operation/Storage Temp.	T _i , T _{STG}	-55 to +150	°C
Range			


Electrical Characteristics @ 25°C Unless Otherwise Specified

Maximum Instantaneous Forward Voltage	VF	1.0V	I _{FM} = 100mA; T _J = 25°C (Note 1)
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	25nA 50μA 2.5uA	$V_{R}=20 \text{Volts}$ $T_{J} = 25^{\circ}\text{C}$ $T_{J} = 150^{\circ}\text{C}$ $V_{R}=75 \text{Volts}$
Typical Junction Capacitance	CJ	4pF	Measured at 1.0MHz, V _R =4.0V
Reverse Recovery Time	T _{rr}	4nS	I_F =10mA V_R = 6V R_L =100 Ω


Note: 1. Valid provided that terminals are kept at ambient temperature

1N4448W

500mW 100 Volts Switching Diode



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
Α	.140	.152	3.55	3.85	
В	.100	.112	2.55	2.85	
С	.055	.071	1.40	1.80	
D		.053		1.35	
Ш	.012	.031	0.30	.78	
G	.006		0.15		
Н		.01		.25	
J		.006		.15	




1N4448W




150

175



Instantaneous Forward Voltage - Volts




Junction Capacitance - pFversus Reverse Voltage - Volts

1N4448W



Instantaneous Reverse Leakage Current - NanoAmperes/ersus Junction Temperature -°C



Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles



Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel:3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): 1N4448WT