

5

4

3

2

1

受控 CONTROLLED DOCUMENT					
编号 P/N	30-9506-29-CUST	版本 Rev	01	日期 Rel'd Date	SEP 17,09

DRAWING NO.
30-9506(10)-29

REVISIONS

01	OFFICIAL RELEASE				Betty 2009.09.16 14:03:57 +0800C
	08-05-09	I	W	T	

D



Description: See Table I
 Part No: See Table I
 Application: Data Extension Cable
 9 Conductor,28 AWG,Shielded
 Crimp Tool: N/A
 Impedance: N/A
 Frequency Range: N/A
 Material: Cable 9 Conductor,28 AWG,Shielded
 DB9 Female
 DB25 Male
 RoHS Compliance: Yes
 Technical Detail: N/A

C

B




TABLE I

P/N	Description	Length
30-9506-29	MODEM CABLE, DB9F TO DB25M,6FT	6FT
30-9510-29	MODEM CABLE, DB9F TO DB25M,10FT	10FT

PIN ASSIGNMENT

DB 9 Female	DB25 Male
1-----8	
2-----3	
3-----2	
4-----20	
5-----7	
6-----6	
7-----4	
8-----5	
9-----22	
G-----G	

DIM OUTLINE

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY IVON.W	DATE 08-05-09
DECIMALS	mm	CHECKED BY IVON.W	DATE 08-05-09
X	± 0.5	APPROVED BY THOMAS	DATE 08-05-09
X.X	± 0.3	U/M	mm
X.XX	± 0.1		
ANGLES	± 0.5°		

CUSTOMER COPY

TITLE
MODEM CABLE, DB9F TO DB25M

SHEET 1 OF 1 | DRAWING NO. 30-9506(10)-29 | SIZE A

A

5

4

3

2

1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions:](#)

[30-9506-29](#)