



NOTES:

1. Electrical Specifications:

- Meets USB 2.0 specifications
- Low level Contact Resistance: 30 mOhm max.
- Insulation Resistance 1000 MOhm min.
- Current Rating: 1.5 A max. @ 25°C
- DWV: 500 VAC/60s at sea level
- Operating Temperature: -40°C to +80°C

2. Material and Finish:

- USB Insulato: PBT, UL 94V-0, Color: White
- USB Overmold: PVC, UL 94V-0, Color: Black
- Metal Shell: Copper Alloy, Nickel plated
- Contact Material: Copper Alloy Contact Finish: 30 u" min. Au over 40 u" min. Nickel

3. Shielded USB Cable Configuration

AWM 2725 AWG28/1p + AWG24/2c, OD: 4.5 mm, Color: black

Directive 2002/95/EC RoHS Compliant

- ⓑ ⓐ
- ⓓ ⓔ
- ⓕ

Cable Length L	Part Number
1 m	17-201021
2m	17-201031
3 m	17-201041
4m	17-201051
4.5 m	17-201061
5 m	17-200861

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: NTS	Dim. in m	
	Name	Title	Approval Date	0 PLC ±0.30	1 PLC ±0.20		Autodesk Inventor	Material: See Notes	
	f	1 x f	Mar/19/2013	Vincent Ke	2 PLC ±0.10	3 PLC ±0.05		Angles ±1°	Title: USB Patch Cord Standard to Standard Version Type A Plug to Type A Plug
	e	1 x e	Jun/11/2012	Vincent ke			D-old	Drawing No.: 17K1A101	
d	1 x d	Sep/13/2011	Vincent ke					Part No.: SEE P/N ABOVE	DIN A3
c	1 x c	Mar/08/2011	Vincent ke						Sheet 1/1
b	1 x b	Jan/19/2009	Vincent ke						
a	original								
Rev.	Changes	Date	Name						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[17-201031](#) [17-201041](#) [17-201061](#)