

4		3		2		1													
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS											
© COPYRIGHT - By -		ALL RIGHTS RESERVED.		E		B		P		LTR		DESCRIPTION		DATE		DWN		APVD	
										B2		ECR-15-012328		19AUG2015		KR		TN	
<div><div><div>HB01AE</div><div><div><div><div>28.8 max</div></div><div><div>9.2</div></div><div><div>3.0 max</div></div></div><div>MARKING FACE</div><div>LEAD LENGTH 20mm MIN</div><div>DESCRIPTION: LEAD MATERIAL: LEAD CROSS-SECTION: HYBRID PROTECTION: MARKING:</div><div>HIGH VOLTAGE THICK FILM RESISTOR. TINNED COPPER WIRE 0.6 +/-0.05 DIA CONFORMAL EPOXY COATING AS SHOWN BELOW ON MARKING FACE</div><div>HB01A VAL. TOL. TCR DATE CODE</div></div></div><div><div><div>HB01AS</div><div><div><div><div>26.0 max</div></div><div><div>8.4 max</div></div><div><div>1.5 max</div></div></div><div>MARKING FACE</div><div>LEAD LENGTH 20mm MIN</div><div>DESCRIPTION: LEAD MATERIAL: LEAD CROSS-SECTION: HYBRID PROTECTION: MARKING:</div><div>HIGH VOLTAGE THICK FILM RESISTOR. TINNED COPPER WIRE 0.6 +/-0.05 DIA SCREEN PRINTED SILICONE COATING AS SHOWN BELOW ON MARKING FACE</div><div>HB01A VAL. TOL. TCR DATE CODE</div></div></div></div></div>																			
<div><div><div><div>R</div></div><div>TYPICAL SCHEMATIC</div></div><div>FOR A SPECIFIC PN FOR A RESISTANCE VALUE AND TOLERANCE, PLEASE REFER TO DMF.</div></div>																			
<div><div><div>RoHS Compliant</div><div><div><div>THIS DRAWING IS A CONTROLLED DOCUMENT.</div><div><div>DIMENSIONS: MM</div><div><div><div><div>0 PLC ± -</div><div>1 PLC ± -</div><div>2 PLC ± -</div><div>3 PLC ± -</div><div>4 PLC ± -</div><div>ANGLES ± -</div></div><div>FINISH -</div></div></div><div><div>MATERIAL -</div></div></div><div><div>DWN 31OCT2005 DAVE KENNEDY</div><div>CHK 01NOV05 J CATCHPOLE</div><div>APVD 01NOV05 J CATCHPOLE</div><div>PRODUCT SPEC -</div><div>APPLICATION SPEC -</div><div>WEIGHT -</div><div>CUSTOMER DRAWING</div></div><div><div><div><div>STE</div>TE Connectivity</div><div>NAME HB01 - -</div><div><div>SIZE A3</div><div>CAGE CODE 00779</div><div>DRAWING NO C-1625958</div><div>RESTRICTED TO -</div></div><div><div>CUSTOMER DRAWING</div><div>SCALE NTS</div><div>SHEET 1 OF 2</div><div>REV B2</div></div></div></div></div></div></div></div>																			

4		3		2		1			
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION					
© COPYRIGHT - By -				ALL RIGHTS RESERVED.					
LOC		DIST		REVISIONS					
E		B		P	LTR	DESCRIPTION	DATE	DWN	APVD
					-	SEE SHEET 1	-	-	-

HB01RE

10.4 max

26.5 max

25.4 min

22.9

3.0 max

MARKING FACE

DESCRIPTION:

LEAD MATERIAL:

LEAD CROSS-SECTION:

HYBRID PROTECTION:

MARKING:

HIGH VOLTAGE THICK FILM RESISTOR.

TINNED COPPER WIRE

0.6 +/-0.05 DIA

CONFORMAL EPOXY COATING

AS SHOWN BELOW ON MARKING FACE

HB01R

VAL.

DATE CODE

TOL.

TCR

HB01RS

8.4 max

26.0 max

25.4 min

22.9

1.5 max

MARKING FACE

DESCRIPTION:

LEAD MATERIAL:

LEAD CROSS-SECTION:

HYBRID PROTECTION:

MARKING:

HIGH VOLTAGE THICK FILM RESISTOR.

TINNED COPPER WIRE

0.6 +/-0.05 DIA

SCREEN PRINTED SILICONE COATING

AS SHOWN BELOW ON MARKING FACE

HB01R

VAL.

DATE CODE

TOL.

TCR

R

TYPICAL SCHEMATIC

FOR A SPECIFIC PN FOR A RESISTANCE VALUE AND TOLERANCE, PLEASE REFER TO DMF.

RoHS Compliant

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

MM

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

FINISH

± -

± -

± -

± -

± -

± -

-

DWN

31OCT2005

DAVE KENNEDY

CHK

01NOV05

J CATCHPOLE

APVD

01NOV05

J CATCHPOLE

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

TE Connectivity

HB01

-

-

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=1625958

-

SCALE

SHEET

REV

NTS

2 OF 2

B2

1470-19 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[HB1100KFZAE](#)