

Product Description

Low Temp Plastic Lead Wire, 24AWG (7x32) Tinned Copper, PVC Insulation, TYPE B MIL-W-16878/1 600V 105C

Technical Specifications

Physical Characteristics (Overall)

Condu	ictor		
AWG	Stranding	Material	No. of Conductors
24	7x32	TC - Tinned Co	opper 1
Cond	uctor Count:	1	
Insula	tion		
	Material	Nomina	Diameter Nominal Wall
PVC ·	- Polyvinyl Ch	nloride 0.044 in	0.01 in
F las			
Elect	rical Cha	racteristics	
Voltag	e		
Volta	ge Rating [V	ני	
600 V	1		
Tom	perature l	Rango	
Non-l	JL Temp Rat	ing: 10	5°C
Mech	nanical C	haracteristi	cs
Bulk	Cable Weight	t: 2	bs/1000ft
Stan	dards		
			-
	WM Style:	N	
Milita	ry Specificatio	on: M	L-W-16878/1
Appl	icable En	vironmenta	l and Other Progra
EU D	irective 2000/	/53/EC Y	es
(ELV)			
EU D	irective 2003/):	/96/EC Y	es
	irective 2011	/65/EU Y	es
(ROH	is ii): irective 2012/	/19/EU	

EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-04-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A
Plenum/Non-Plenum	
Plenum (Y/N):	No
Part Number	

i urt iturit.

ltem #	Color	UPC	Length	Footnote
8504 010100	Black	612825210313	100 ft	
8504 0101000	Black	612825210320	1,000 ft	Р
8504 006100	Blue, Light	612825210207	100 ft	
8504 0061000	Blue, Light	612825210214	1,000 ft	Р
8504 001100	Brown	612825210054	100 ft	
8504 0011000	Brown	612825210061	1,000 ft	Р
8504 008100	Gray	612825210238	100 ft	
8504 0081000	Gray	612825210245	1,000 ft	Р
8504 005100	Green, Dark	612825210177	100 ft	
8504 0051000	Green, Dark	612825210184	1,000 ft	Р
8504 003100	Orange	612825210115	100 ft	
8504 0031000	Orange	612825210122	1,000 ft	Р
8504 002100	Red	612825210085	100 ft	
8504 0021000	Red	612825210092	1,000 ft	Р
8504 0071000	Violet	612825210221	1,000 ft	Р
8504 009100	White	612825210269	100 ft	
8504 0091000	White	612825210276	1,000 ft	Р
8504 004100	Yellow	612825210146	100 ft	
8504 0041000	Yellow	612825210153	1,000 ft	Р

Footnote:

P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

History

Update and Revision: Revision Number: 0.251 Revision Date: 04-08-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.