

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC  
ES

DIST  
00

REVISIONS

| P | LTR | DESCRIPTION               | DATE    | DWN | APVD |
|---|-----|---------------------------|---------|-----|------|
|   | B2  | REVISED PER ECO-11-005033 | 24MAR11 | RK  | HMR  |

0.6

1.0

4.0

6.6

1.7 REF

2.0 PITCH

1.0

TRADE MARK

CIRCUIT NO. 1

2 REF

2.0 PITCH

3P ONLY

2.0 PITCH

4P ONLY

2.0 PITCH

2P ONLY

NOTES:

1

MATERIAL : 66 NYLON (UL94V-0)

2. PRODUCT SPEC.: 108-5408

3. APPLICATION SPEC.: 114-5179

4

7-179228-3 WAS OBSOLETE.

5

CAVITY NUMBER LOCATED. (OPTIONAL)

|                    |                    |                    |                    |     |    |      |      |
|--------------------|--------------------|--------------------|--------------------|-----|----|------|------|
| 7-179228-5         | 5-179228-5         | 3-179228-5         | 1-179228-5         | 15  | 28 | 30.8 | 32.0 |
| 7- <div>▲</div> -4 | 5- <div>▲</div> -4 | 3- <div>▲</div> -4 | 1- <div>▲</div> -4 | 14  | 26 | 28.8 | 30.0 |
| 7- <div>▲</div> -3 | 5- <div>▲</div> -3 | 3- <div>▲</div> -3 | 1- <div>▲</div> -3 | 13  | 24 | 26.8 | 28.0 |
| 7--2               | 5--2               | 3--2               | 1--2               | 12  | 22 | 24.8 | 26.0 |
| 7--1               | 5--1               | 3--1               | 1--1               | 11  | 20 | 22.8 | 24.0 |
| 7--0               | 5--0               | 3--0               | 1--0               | 10  | 18 | 20.8 | 22.0 |
| 6--9               | 4--9               | 2--9               | --9                | 9   | 16 | 18.8 | 20.0 |
| 6--8               | 4--8               | 2--8               | --8                | 8   | 14 | 16.8 | 18.0 |
| 6--7               | 4--7               | 2--7               | --7                | 7   | 12 | 14.8 | 16.0 |
| 6--6               | 4--6               | 2--6               | --6                | 6   | 10 | 12.8 | 14.0 |
| 6--5               | 4--5               | 2--5               | --5                | 5   | 8  | 10.8 | 12.0 |
| 6--4               | 4--4               | 2--4               | --4                | 4   | 6  | 8.8  | 10.0 |
| 6--3               | 4--3               | 2--3               | --3                | 3   | 4  | 6.8  | 8.0  |
| 6-179228-2         | 4-179228-2         | 2-179228-2         | 179228-2           | 2   | 2  | 4.8  | 6.0  |
| BLACK              | YELLOW             | BLUE               | NATURAL            | POS | A  | B    | C    |

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
mm

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

± -

± -

± -

± -

± -

± 3°

FINISH

GENERAL TOLERANCE

0<\* ≤ 10 : ±0.2

10<\* ≤ 30 : ±0.25

30<\* ≤ 100 : ±0.3

ANGLES : ±3°

MATERIAL

SEE NOTE 

1

DWN  
T.FURUYA

CHK  
S.KUBOUCHI

APVD  
S.KUBOUCHI

PRODUCT SPEC  
—

APPLICATION SPEC  
—

WEIGHT  
—

12NOV1993

15NOV1993

15NOV1993

TE Connectivity

CRIMP TYPE II RECEPTACLE HOUSING  
(AMP CT CONNECTOR 2mm PITCH)

SIZE  
A3

CAGE CODE  
00779

DRAWING NO  
C-179228

RESTRICTED TO  
—

CUSTOMER DRAWING

SCALE  
NTS

SHEET  
1 OF 1

REV  
B2

1470-19 (3/11)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-179228-4](#)