

SPECIFICATION CONTROL DRAWING


55AC6262

TITLE TWO CONDUCTOR CABLE, SHIELDED, JACKETED,
LIGHTWEIGHT, 600 VOLT

Date 01-11-03

Revision A

This specification sheet forms a part of the latest issue of Raychem Specification 55A



CABLE CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (inch)		OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lb/1000 ft.)
			MINIMUM	MAXIMUM	NOMINAL	MAXIMUM	
55AC6262-30-*	30	38	.005	.010	.081	.086	5.7
55AC6262-28-*	28	38	.005	.010	.087	.092	6.6
55AC6262-26-*	26	38	.005	.010	.097	.102	8.3
55AC6262-24-*	24	38	.005	.010	.107	.112	10.2
55AC6262-22-*	22	38	.005	.010	.119	.125	12.9
55AC6262-20-*	20	38	.005	.010	.133	.142	16.9

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature
VOLTAGE RATING: 600 volts (rms)

BLOCKING: 200 ± 3°C for 6 hours

CROSSLINKED VERIFICATION: 300 ± 5°C for 6 hours

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz

FLAMMABILITY:

Procedure 1, 3 seconds (maximum); 3 in. (maximum);
no flaming of facial tissue

JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 50% (minimum)

Tensile Strength, 5000 lbf/in² (minimum)

JACKET FLAWS:

Spark Test, 1500 volts (rms), 100% test

Impulse Dielectric Test, 6.0 kV (peak), 100% test

LOW TEMPERATURE-COLD BEND: -55 ± 5°C for 4 hours

SHIELD COVERAGE: 90% (minimum)

VOLTAGE WITHSTAND TEST: (POST ENVIRONMENTAL)
1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:

The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.

Example: AWG 20, white and blue component wires;
white jacket: 55AC6262-20-9/6-9

NOTE: Nominal values are for information only.
Nominal values are not requirements.

This cable shall meet all constructional requirements of M27500 (AWGSC2S23)

COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[55AC6262-24-9/96-9CS2275](#) [55AC6262-22-9/96-9CS2275](#)