


Active module - UM- 8 RM-S-G24/21/PLC-MSTB - 2311030

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Relay module, with 8 miniature relays, one changeover contact each, plugged in, for 24 V DC (incl. relay)



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 134958
GTIN	4046356134958

Technical data

Dimensions

Width	61 mm
Height	126 mm
Depth	146 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

Input data

Nominal input voltage U_N	24 V DC (# 10 %)
Typical input current at U_N	200 mA (200 mA supply / ≤ 20 mA input current per signal)

Output data

Contact type	Single contact, 1-PDT
Maximum switching voltage	150 V AC/DC (Maximum switching voltage of 230 V AC: the maximum switching voltage of 230 V is only permitted if the same fuse circuit is used. The outputs are not suitable for switching different outer conductors.)
Limiting continuous current	4 A

General

With components	yes
Degree of protection	IP00
Mounting position	any

Connection data for connection 1

Connection name	Controller level
Connection in acc. with standard	IEC 60603-13

Active module - UM- 8 RM-S-G24/21/PLC-MSTB - 2311030

Technical data

Connection data for connection 1

Connection method	IDC/FLK pin strip
Number of connections	1
Number of positions	14

Connection data for connection 2

Connection name	Field level
Connection method	Screw connection
Conductor cross section solid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Number of connections	1
Number of positions	12

Connection data for connection 3

Connection name	Supply
Connection method	Screw connection
Conductor cross section solid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Number of connections	1
Number of positions	2

Connection data for connection 4

Connection name	DEROG
Connection method	Screw connection
Conductor cross section solid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Number of connections	1
Number of positions	3

Standards and Regulations

Designation	Air clearances and creepage distances, input/output
Standards/regulations	DIN EN 50178: 1998-04
Rated insulation voltage	260 V
Rated surge voltage	6 kV (1.2/50 µs)
Insulation	Reinforced insulation
Degree of pollution	2
Overvoltage category	III
Designation	Air and creepage distances, output/output
Standards/regulations	DIN EN 50178: 1998-04
Rated insulation voltage	260 V
Rated surge voltage	2.3 kV (1.2/50 µs)

Active module - UM- 8 RM-S-G24/21/PLC-MSTB - 2311030

Technical data

Standards and Regulations

Insulation	Functional insulation
Degree of pollution	2
Overvoltage category	II

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.A*30.B.01742
-----	---	--------------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2311030](#)