

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC

DIST

CM

00

REV

LTR

DESCRIPTION

DATE

DWN

APVD

C

REVISED

PER

ECO-12-007810

28JUL12

KH

SM

1

UNIT ACCEPTS 1.14 [.045] SQUARE OR ROUND POST.

2

UNIT ACCEPTS STANDARD SL-156 CONTACTS.

3

UNIT ACCEPTS KEYING PLUG 640254-1 AND KEYING PIN 640255-1.

4

CIRCUIT I.D. NUMBER(S),TO BE LOCATED SEQUENTIALLY AS SHOWN.

5

DIMENSIONS IN BRACKETS ARE IN INCHES.

6

ACCEPTS UP TO .110 INCH INSULATION WIRE.

7

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

2.41
[.095]
TYP

1.37
[.054]

1.37
[.054]
TYP

3.96
[.156]
TYP

16.76
[.660]

6.35
[.250]

0.13/25.40
[.005/1.000]

1

2

3

4

A
REF

3-DIMENSIONAL MODEL
NTS

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± 0.13 [.005]

4 PLC ± -

ANGLES ± 0°30'

FINISH -

MATERIAL
NYLON,UL94V-0,NAT

DIM A

NO. OF
CIRCUITS

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
L. McEACHIN
28MAR00

CHK
J. ELLIS
28MAR00

APVD
J. ELLIS
28MAR00

PRODUCT SPEC

APPLICATION SPEC

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

WEIGHT

A1

00779

647400

CUSTOMER DRAWING

SCALE
4:1

SHEET
1

OF
1

REV
C

4805 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-647400-2](#)