

Specification Sheet

Part Number: CTN1140STD



Convoluted Tubing, Slit, 1.25" Dia, PA6, Black with Gray Stripe, 250 ft/carton

Article Number	169-60005
Type	CTN1140
Color	Black with Gray Stripe (BKSTGY)
Features & Benefits	<ul style="list-style-type: none">• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture.• Tubing protects cables and wires against automotive fluids and vibration wear.• Weather resistant material provides protection against water, snow, ice, and the effects of heat or cold.• Nylon material is formulated to withstand high temperatures.• Lateral slit allows fast and easy insertion of wires.
Quantity Per	carton

Product Description	Convoluted tubing provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. It also can serve to protect valuable wiring circuits. HellermannTyton's convoluted tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat or cold on cables and wires. Available in standard, bulk, and dispenser box packaging. Material is slit.
Short Description	Convoluted Tubing, Slit, 1.25" Dia, PA6, Black with Gray Stripe, 250 ft/carton
Global Part Name	CTN1140-PA6-BK
Technical Description	Convoluted Tubing, Slit, 1-1/4" Dia., PA6, Black w/Gray Stripe
Length L (Imperial)	250.0
Length L (Metric)	76.2
Variant	Slit
Inner Diameter D (Imperial)	1.257
Inner Diameter D (Metric)	31.93
Diameter D (imperial)	1.50
Diameter D (metric)	38.10
Outside Diameter OD(Imperial)	1.50
Outside Diameter OD(metric)	38.10

Nominal Diameter (Imperial)	1.25
Nominal Diameter (Metric)	31.75
Wall Thickness WT (Imperial)	0.006
Wall Thickness WT (Metric)	0.152
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)