



Product: [8241](#) 

75 Ohm Analog Video Coax, RG-59, 23 AWG Solid BCCS, 95% BC Braid, PVC Jkt, CM

Product Description

75 Ohm Analog Video Coax, RG-59, 23 AWG Solid Bare Copper Covered Steel Conductor , PE Insulation, 95% Bare Copper Braid Shield, PVC Jacket, CM

Technical Specifications

Product Overview

| | |
|------------------------|-----------------------|
| Suitable Applications: | Standard analog video |
|------------------------|-----------------------|

Construction Details

| | |
|----------|----|
| RG Type: | 59 |
|----------|----|

Conductor

| AWG | Stranding | Nom. Diameter | Material |
|-----|-----------|---------------|----------------------------------|
| 23 | Solid | 0.023 in | BCCS - Bare Copper Covered Steel |

Insulation

| Material | Nom. Diameter |
|-------------------|---------------|
| PE - Polyethylene | 0.146 in |

Outer Shield Material

| Outer Shield Type | Material | Coverage |
|-------------------|------------------|----------|
| Braid | Bare Copper (BC) | 95% |

Outer Jacket Material

| Material | Nom. Diameter |
|--------------------------|---------------|
| PVC - Polyvinyl Chloride | 0.240 in |

Electrical Characteristics

Attenuation

| Frequency | Nom. Attenuation |
|-----------|------------------|
| 1 MHz | 0.6 dB/100ft |
| 10 MHz | 1.1 dB/100ft |
| 50 MHz | 2.4 dB/100ft |
| 100 MHz | 3.4 dB/100ft |
| 200 MHz | 4.9 dB/100ft |
| 400 MHz | 7.0 dB/100ft |
| 700 MHz | 9.7 dB/100ft |
| 900 MHz | 11.1 dB/100ft |
| 1000 MHz | 12.0 dB/100ft |

Power Rating

| Frequency [MHz] | Max. Power Rating [W] |
|-----------------|-----------------------|
| 50 MHz | 470 W |
| 100 MHz | 310 W |
| 300 MHz | 160 W |

| | |
|-----------|-------|
| 500 MHz | 115 W |
| 1,000 MHz | 76 W |

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Impedance |
|--------------------|-----------------------|---------------------------------|----------------|
| 49 Ohm/1000ft | 2.6 Ohm/1000ft | 20.4 pF/ft | 75 Ohm |

Voltage

| UL Voltage Rating | Non-UL Voltage Rating |
|--------------------------------|-----------------------|
| 300 V (CM), 30 V (UL AWM 1354) | 1700 V |

Mechanical Characteristics

Temperature

| UL Rating | Operating |
|-----------|----------------|
| 75°C | -30°C to +75°C |

Bend Radius

| Installation Min. |
|-------------------|
| 2.4 in |

| | |
|--------------------|---------------|
| Bulk Cable Weight: | 37 lbs/1000ft |
| Max. Pull Tension: | 63 lbs |

Standards and Compliance

| | |
|---------------------------------|---|
| Environmental Suitability: | Indoor/Outdoor, Indoor |
| Sustainability: | CA Prop 65 |
| Flammability / Fire Resistance: | UL1685 UL Loading |
| NEC / UL Compliance: | CM |
| AWM Compliance: | 1354 |
| CEC / C(UL) Compliance: | CM |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Plenum Number: | 88241, 82241 |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.307 Revision Date: 08-25-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[8241 0101000](#) [8241 010U1000](#) [8241 010U500](#) [8241 002U1000](#) [8241 010100](#) [8241 010500](#) [8241 006U1000](#) [8241 009U1000](#) [8241 0105000](#) [8241 0102000](#) [8241 003U1000](#) [8241 005U1000](#) [8241 004U1000](#)