



- △1 MATERIAL: 0.2mm THICK CuNiSi ALLOY
- △2 FINISH: PRE-PLATED WITH 1.00µm MIN BRIGHT TIN
- △3 MATERIAL ID FEATURE IN "DOWN" POSITION
4. THIS PRODUCT TO BE VALIDATED TO GMW3191, TEMP CLASS T3 AND VIBRATION CLASS VI
5. THIS PRODUCT IS DESIGNED TO BE COMPATIBLE WITH SEALED APPLICATIONS
6. NOTE DELETED
7. NORMAL FORCE 240 GRAMS REFERENCE.
8. BULGE PERMISSIBLE UNDER ORIENTATION FEATURE.
9. TERMINAL HAS NYE LUBRICANTS NYETACT 568J-50-UV PERFORMANCE LUBE/GREASE APPLIED. THIS IS A WHITISH COLORED LUBE. AMOUNT AND VISIBILITY MAY VARY.
- △10 NOT INTENDED FOR SEALED APPLICATIONS.
- △11 SEALING CAPABILITY MUST BE EVALUATED ON AN APPLICATION BASIS.



REELING DIRECTION

4805 (3/13)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2035170-2](#)