



- NOTES
- CONNECTOR WILL ACCEPT FLEXIBLE PRINTED CIRCUIT OR FLAT FLEXIBLE CABLE ON 2.54 [0.100] CENTERS IN A THICKNESS RANGE OF 0.127 TO 0.381 [0.005 TO .015] IN CONTACT AREA
  - STAND-OFFS PREVENT SOLVENT ENTRAPMENT
  - LEAD-IN ON PINS FOR EASE OF INSERTION INTO BOARD
  - SEQUENTIAL CONTACTS REDUCE CABLE INSERTION FORCE
  - STABILIZING WING MAY BE REMOVED BY CUSTOMER IF NECESSARY
  - ALTERNATING CONTACT FORM RETAINS CONNECTOR IN P.C. BOARD DURING SOLDER OPERATION
  - ACCEPTS CABLE OR CIRCUITRY WITH EXPOSED CONDUCTORS FACING TOWARD OR AWAY FROM THE BOARD SURFACE
  - REFER TO APPLICATION SPEC 114-2062
  - MATERIAL  
HOUSING : GLASS REINFORCED POLYESTER  
THERMOPLASTIC UL 94 VO RATED, BLACK  
CONTACT : PHOS BRONZE WITH MATTE TIN FINISH.
  - AREA INDICATED SHALL MEET SOLDERABILITY SPEC 109-11-1
  - OBsolete PARTS: OBsolete CIS STREAMLINING PER D.RENAUD/D.SINISI

NUMBER 520314  
 METRIC  
 DIMENSIONS IN MM [INCHES]. DO NOT SCALE PRINT  
 PRINT DIST

		LEAD FREE			SUPERSEDED	
OBsolete	Part No	Packing	B	A	POS	Part No
<del>7-520314-2</del>	60.78 [2.393]	58.62 [2.308]	22	2-520314-2		
<del>7-520314-1</del>	58.24 [2.293]	56.08 [2.208]	21	2-520314-1		
<del>7-520314-0</del>	55.70 [2.193]	53.54 [2.108]	20	2-520314-0		
6-520314-9	53.16 [2.093]	51.00 [2.008]	19	1-520314-9		
<del>6-520314-8</del>	50.62 [1.993]	48.46 [1.908]	18	1-520314-8		
6-520314-7	48.08 [1.893]	45.92 [1.808]	17	1-520314-7		
6-520314-6	45.54 [1.793]	43.38 [1.708]	16	1-520314-6		
6-520314-5	43.00 [1.693]	40.84 [1.608]	15	1-520314-5		
<del>6-520314-4</del>	40.46 [1.593]	38.30 [1.508]	14	1-520314-4		
6-520314-3	37.92 [1.493]	35.76 [1.408]	13	1-520314-3		
6-520314-2	35.38 [1.393]	33.22 [1.308]	12	1-520314-2		
6-520314-1	32.84 [1.293]	30.68 [1.208]	11	1-520314-1		
6-520314-0	30.30 [1.193]	28.14 [1.108]	10	1-520314-0		
5-520314-9	27.76 [1.093]	25.60 [1.008]	9	520314-9		
5-520314-8	25.22 [0.993]	23.06 [0.908]	8	520314-8		
5-520314-7	22.68 [0.893]	20.52 [0.808]	7	520314-7		
5-520314-6	20.14 [0.793]	17.98 [0.708]	6	520314-6		
5-520314-5	17.60 [0.693]	15.44 [0.608]	5	520314-5		
5-520314-4	15.06 [0.593]	12.90 [0.508]	4	520314-4		
<del>5-520314-3</del>	12.52 [0.493]	10.36 [0.408]	3	520314-3		
5-520314-2	9.98 [0.393]	7.82 [0.308]	2	520314-2		

S3 ECR-10-022530		KK	HMR	07FEB11	Copyright ©1993		Copyright ©1993		TE Connectivity	
S2 ECO-10-000445		KK	AEG	11JAN10	TE MFG (S) PTE LTD.		ALL RIGHTS RESERVED.			
S1 REVISED AS PER ECR-06-04332		PM	KS	21FEB06	(WIRE RANGE)	(INSULATION DIA.)	(NAME)			
S REVISED FRO00-0011-04		SD	PCH	19FEB04	mm <sup>2</sup> (AWG - )	mmØ	TRIOMATE HORIZONTAL CABLE ENTRY			
R REVISED DY/EC/0920		LWY	SL	13.12.93	(MATERIAL)	(FINISH) CONTACTS	FOR 1.57 [0.062] THK P.C. BOARD			
Q REDRAWN DY/EC/0784		LWY	SL	30.7.93	△	MATTE TIN/LEAD PLATED	(GENERAL TOLERANCE)	SIZE	LOC	(No.)
LTR (REVISION RECORD)		DR	CHK	DATE	DR. WYLEE 30.7.93	DE. A.SOH	±.38	A3	DY	520314
					CHK. SALLY 30.7.93	APP. PETER de JONG	[±.015]	(SCALE)	REV.	SHEET
							6:1	S3	1 OF 1	

(CUSTOMER DRAWING)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-520314-6](#)