

	2

\_OC

ΑI

DIST			REVISIONS			
_	Ρ	LTR	DESCRIPTION	DATE	DWN	APVD
		B13	Released As per ECR-09-005436	9-Mar-2009	CJ	TS
		B14	ECR-11-002636	05APR2011	SR	AR

PN 1-1,2-1,3-1,4-1,5-1,1-2,2-2,3-2 4-2,5-2,6-1,4-3,1-8,2-8,3-8,4-8,5-8, 4-9,2-9,3-9,4-9 & 5-9

## NOTES

MATERIAL SEE TABLE

SURFACE SEE TABLE

ASSEMBLY WEIGHT SEE TABLE

A PACKAGING: 50 PIECES IN POLY-BAG 0-1243085-8

ACKAGING: 500 PIECES IN POLY-BAG 0-1243085-8

A PACKAGING: 10 PIECES IN POLY-BAG 0-1243085-8

CROSS-SECTION MARKING

	OBSOLETE	OBSOLETE	OBSOLETE															6		SCALE 4:	<u>^</u>		
	OBS	OBS	OBS														$\boxed{3}$	1	2		_7		
	1	1	1	1	1	1	1	1	1	1	1	1	1	1	Catch Sprin	9		Stainless Steel				2	
	1														Pin Contact	1.5 mm <sup>2</sup>	0.00062	Ms/Brass	Ag/Ni	1.8 3.0	4		
		1													Pin Contact	4.0 mm <sup>2</sup>	0.00059	Ms/Brass	Ag/Ni	2.4 3.2	6		
					1										Pin Contact	2.5 mm <sup>2</sup>	0.00067	Ms/Brass	Au	2.2 3.2	5		
						1									Pin Contact	1.5 mm <sup>2</sup>	0.00067	Ms/Brass	Au	1.8 3.0	4		
							1								Pin Contact	0.75-10 mm²	0.00063	Ms/Brass	Au	1.45 2.6	3		
								1							Pin Contact	0.5 mm <sup>2</sup>	0.00062	Ms/Brass	Au	1.1 2.6	2		
									1						Pin Contact	0.14-0.37 mm <sup>2</sup>	0.00061	Ms/Brass	Au	0.9 2.6	1	1	
										1					Pin Contact	2.5 mm <sup>2</sup>	0.00065	Ms/Brass	Ag/Cu	2.2 3.2	5		
											1				Pin Contact	1.5 mm <sup>2</sup>	0.00067 Ms/Bras	Ms/Brass	Ag/Cu	1.8 3.0	4		
												1			Pin Contact	0.75-10 mm <sup>2</sup>	0.00063	Ms/Brass	Ag/Cu	1.45 2.6	3		
													1		Pin Contact	0.5 mm <sup>2</sup>	0.00062	Ms/Brass	Ag/Cu	1.1 2.6	2		
OBSOLETE-			4												Pin Contact	0.14-0.37 mm <sup>-2</sup>	0.00061	Ms/Brass		0-9 2.6			
OBSOLE TE-				1											Pin Contact	0.14-0.37 mm <sup>-2</sup>	0.00065	Fe	Au	0-9 2.6			В
														1	Pin Contact	0.14-0.37 mm <sup>2</sup>	0.00067	Ms/Brass	Ag/Cu	0-9 2.6	1		
2 [	4 2	6-1		1-3	5-2 /5	4-2 4-2 5 4-9	3-2	5	1-2	5-1	4-1	<u>/</u> 5\	2-1	<u>/</u> 5\	DESC	RIPTION	WEIGHT IN (Kg)	MATERIAL	SURFACE	ØA ØB	CROSS SECTION MARKING	POS	
	HND-C-Sti.Ag/Ni.1,5 mm 2	HND C Sti.Ag/Ni.4.0 mm 2	HN.D-C-Sti.CuNi.0,14 -0.37 mm <sup>2</sup>	HN.D-C-Sti.Fe.Au.0.14 -0.37 mm <sup>2</sup>	HN.D-C-Sti.Au.2.5 mm 2	HN.D-C-Sti.Au.1.5 mm <sup>2</sup>	HN.D-C-Sti.Au.0.75-1.00 mm 2	HN.D-C-Sti.Au.0,5 mm 2	HN.D-C-Sti.Au.0.14 -0.37 mm 2	HN.D-C-Sti.Ag.2.5 mm 2	HN.D-C-Sti.Ag.1.5 mm 2		🛱 HN.D-C-Sti.Ag.0.5 mm 2	HN.D-C-Sti.Ag.0.14 -0.37 mm 2	DWN	23.07.1997							
								0 PL 1 PL 2 PL 3 PL 4 PL 4 PL	C C C C E S	ANCES ISE SF ±- ±- ±- ±- ±-	UNLE ECIF	:ss Ied: 1	Braun CHK Schnurpf APVD PRODUCT SPEC 108-74 APPLICATION 114-74	- + 018 spec	NAME PIN CONTACT SERIES HN.D - SIZE   CAGE CODE   DRAWING NO   RE			† y RESTRICT	ED TO	A			
				M/	ATERI <i>i</i>	AL ^				FINISH					WEIGHT	weight - A 2 00779			C=1105050 -				
								-						CUSTOMER DRAWING				1 Rev	14				

D

С

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 5-1105050-2