



## Heyco® TPE Liquid Tight Hole Plugs

### Standard 85 Durometer Plugs

Maximum Panel Thickness .125" (3,2 mm)

Mounting Hole Diameter Range: .500" (12,7 mm) to 1.375" (34,9 mm)

- Oil tight, rain tight, submersible.
- UL certified for outdoor applications.
- Install with fingertip pressure (no tool required).
- Multiple nominal sizes fit .500" (12,7 mm) to 1.000" (25,4 mm) true size mounting holes.
- Three trade sizes fit 1/2" to 1" knock-out holes.
- Lock firmly in boxes from .03" (0,8 mm) to .13" (3,2 mm) thick.
- True sizes are UL recognized under Underwriters' Laboratories File E51579 and CSA certified by Canadian Standard Association File 8919.
- Trade sizes are UL listed under Underwriters' Laboratories File E51579 and CSA certified by Canadian Standard Association File 081067C. Now certified for **NEMA 4 and 4X applications.**

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	UL or RA	PART DIMENSIONS					
in.	mm.				A Head Diameter		B Overall Height		C Head Thickness	
.500	12,7	<b>3830</b>	KOS LT 500	RA	.91	23,1	.45	11,4	.29	7,4
.625	15,9	<b>3834</b>	KOS LT 625	RA	1.03	26,2	.47	11,9	.31	7,9
.750	19,1	<b>3831</b>	KOS LT 750	RA	1.15	29,2	.51	13,0	.35	8,9
.875	22,2	<b>3833</b>	KOS LT 1/2	UL	1.23	32,5	.50	13,5	.36	9,1
1.000	25,4	<b>3832</b>	KOS LT 1000	RA	1.41	35,8	.56	14,2	.40	10,2
1.093	27,8	<b>3835</b>	KOS LT 3/4	UL	1.53	38,6	.55	14,0		
1.375	34,9	<b>3837</b>	KOS LT 1	UL	1.78	45,2	.57	14,5	.42	10,7

Available in black only.

### Low 75 Durometer Plugs


Maximum Panel Thickness .125" (3,2 mm)

Mounting Hole Diameter Range: .875" (22,2 mm) to 1.375" (34,9 mm)

MOUNTING HOLE DIAMETER*		PART NO.		DESCRIPTION	UL or RA	PART DIMENSIONS*					
in.	mm.	Black	Gray			A Head Diameter		B Overall Height		C Head Thickness	
.875	22,2	<b>3833FN</b>	<b>3833FP</b>	KOS LT 1/2 LD	UL	1.23	32,5	.53	13,5	.36	9,1
1.093	27,8	<b>3835FN</b>	<b>3835FP</b>	KOS LT 3/4 LD	UL	1.53	38,6	.55	14,0	.40	10,2
1.375	34,9	<b>3837FN</b>	<b>3837FP</b>	KOS LT 1 LD	UL	1.80	45,2	.56	14,3	.42	10,7

Standard colors black and gray.

\*Consult Heyco for other Liquid Tight Hole Plug sizes in Low Durometer material.



Quick Specs

Material	85 Durometer 75 Durometer	TPE-Hardness 85 Shore A TPE-Hardness 75 Shore A
Certifications	Trade Sizes (1/2, 3/4, 1)	UL Listed under Underwriters' Laboratories File E51579 CSA Certified by Canadian Standard Association File 081067C
	True Sizes (all others)	RA Recognized under Underwriters' Laboratories File E51579 CSA Certified by Canadian Standard Association File 8919
Flammability Rating	94V-0	
Temperature Range	-81°F (-60°C) to 275°F (135°C)	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Heyco:](#)

[3835](#) [3833](#) [3837](#) [3834](#) [3830](#) [3831](#) [3832](#) [3835FN](#) [3833FN](#) [3837FP](#) [3837FN](#) [3835FP](#) [3833FP](#) [3832-P](#) [3833EU](#)