



Product: [9916](#)

Lead Wire, #16 Str TC, PVC Ins, AWM 1007 AWM 1569

[Request Sample](#)

Product Description

Low Temp Plastic Lead Wire, 16AWG (26x30) Tinned Copper, PVC Insulation, AWM 1007 AWM 1569 CSA TYPE TR-64 TRSR-64

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors	No. of Pairs
16	26x30	TC - Tinned Copper	1	[Delete]
			[Delete]	

Conductor Count:

Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.092 in	0.016 in	0.015 in

Outer Jacket Material

Material
No Jacket

Construction and Dimensions

Cabling

Twists
6 twist/ft

Electrical Characteristics

Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V	300 V

Temperature Range

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C

Mechanical Characteristics

Bulk Cable Weight:	11.5 lbs/1000ft
--------------------	-----------------

Standards

UL Rating:	300V RMS, 80°C and 300V, 105°C
UL AWM Style:	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
CSA Rating:	300V RMS, 105°C
CSA AWM Specification:	TRSR-64
CSA Type:	TRSR-64

Military Specification:	N/A
-------------------------	-----

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	UPC	Length	Footnote
9916 010100	Black	612825261988	100 ft	
9916 0101000	Black	612825261995	1,000 ft	P
9916 0105000	Black	612825262008	5,000 ft	P
9916 013100	Blue, Dark	612825262015	100 ft	
9916 0131000	Blue, Dark	612825262022	1,000 ft	P
9916 001100	Brown	612825261797	100 ft	
9916 0011000	Brown	612825261803	1,000 ft	P
9916 0081000	Gray	612825261933	1,000 ft	P
9916 005100	Green, Dark	612825261896	100 ft	
9916 0051000	Green, Dark	612825261902	1,000 ft	P
9916 0031000	Orange	612825261858	1,000 ft	P
9916 002100	Red	612825261827	100 ft	
9916 0021000	Red	612825261834	1,000 ft	P
9916 0025000	Red	612825261841	5,000 ft	P
9916 007100	Violet	612825261919	100 ft	
9916 0071000	Violet	612825261926	1,000 ft	P
9916 009100	White	612825261940	100 ft	
9916 0091000	White	612825261957	1,000 ft	P
9916 0095000	White	612825261964	5,000 ft	P
9916 004100	Yellow	612825261865	100 ft	
9916 0041000	Yellow	612825261872	1,000 ft	P

Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.
-----------	---

History

Update and Revision:	Revision Number: 0.277 Revision Date: 12-19-2019
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.