
## UNCONTROLLED DOCUMENT

PIN 1 ¬

PIN 6

- PIN 16

PIN 9



DIGIT DETAIL

<u>→</u> 20.00 [0.787]	8,	
	A A	B
Ø0.51 [Ø0.02 (16 PLS.)	<u> </u>	
15,24 [0,600]	Ŭ LOP	RDP
A	3,5,11,16	
A B C	COMMON ANODE	
1 14 12	10 4 2 13 9 6	
NO	PIN: 7, B & 15	

## PART NUMBER LDS—A814RI—SI

E.C.N. NUMBER AND REVISION COMMENTS DATE
E.C.N. #11451. 10.25.07

REV.

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=10mA					
PARAMETER	MIN	ΤΥP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		636		nm	_
FORWARD VOLTAGE		2.0	2.5	$V_f$	
reverse voltage	5.0			٧r	I <sub>r</sub> = 100μΑ
AXIAL INTENSITY		13000		Jucd	I <sub>f</sub> =10mA
EMITTED COLOR:	RED				
FACE COLOR:	GRAY				
SEGMENT COLOR:	MILKY	WHITE DIFFUS	ED		

## LIMITS OF SAFE OPERATION AT 25°C PER SEGMENT

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	m₩
DERATE FROM 25°C	- 1.6	mW∕°C
OPERATING, STORAGE TEMP.	- 40 TO +85	<b>'</b> C
SOLDERING TEMP.	+ 260	<b>'</b> C
2.0mm FROM BODY		3 SEC. MAX

\* t<10µS

UNCONTROLLED DOCUMENT

\*\*UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.5 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECINAL PRECISION MAX.= +0.00 (±0.004). PRECISION MAX.= +0.00 (±0.005).

A LDS—A814RI—SI

0.80" SEVEN SEGMENT, LED DISPLAY, 636nm RED CHIPS, GRAY FACE WITH WHITE SEGMENTS, COMMON ANODE, 16 PINS. CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF
LUMEX NG. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX
INC., THE HADDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION
CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR
IN PART FROM DESCLISURE AND DISSEMNATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT
SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 7.3.03
PAGE: 1 OF 1
BC SCALE: N/A

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

LDS-A814RI-SI