

LOC	DIST	REVISIONS					
A1	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
			B3	REWORKED PER ECR 09-026789	08DEC2009	MH	BR
			B4	ECR-11-002636	05APR2011	SR	AR



PN 1-1,2-1,3-1,4-1,5-1,1-2,2-2,3-2
4-2,5-2,6-1,4-3,1-8,2-8,3-8,4-8,5-8,
4-9,2-9,3-9,4-9 & 5-9


$$\varnothing A_{-0.05}$$


A dimension line with arrows at both ends, labeled $B+0.05$ above it.

NOTES

- | | |
|---|---|
| 1 | MATERIAL SEE TABLE |
| 2 | SURFACE SEE TABLE |
| 3 | ASSEMBLY WEIGHT SEE TABLE |
| 4 | PACKAGING: 50 PIECES IN POLY-BAG 0-1243085-8 |
| 5 | PACKAGING: 500 PIECES IN POLY-BAG 0-1243085-8 |
| 6 | PACKAGING: 10 PIECES IN POLY-BAG 0-1243085-8 |
| 7 | CROSS-SECTION MARKING |

PN 1-1,2-1,3-1,4-1,5-1,1-2,2-2,3-2
4-2,5-2,6-1,4-3,1-8,2-8,3-8,4-8,5-8,
4-9,2-9,3-9,4-9 & 5-9



OBSOLETE		OBSOLETE	OBSOLETE											△3	△1	△2	△7			
1	1	1	1	1	1	1	1	1	1	1	1	1	1	Catch Spring		Stainless Steel				2
														Socket Contact 1.5 mm ²	0.00062	Brass	Ag/Ni	1.8	3.0	4
	1													Socket Contact 4.0 mm ²	0.00059	Brass	Ag/Ni	2.4	3.2	6
				1										Socket Contact 2.5 mm ²	0.00067	Brass	Au	2.2	3.2	5
					1									Socket Contact 1.5 mm ²	0.00067	Brass	Au	1.8	3.0	4
						1								Socket Contact 0.75-10 mm ²	0.00063	Brass	Au	1.45	2.6	3
							1							SocketContact 0.5 mm ²	0.00062	Brass	Au	1.1	2.6	2
								1						Socket Contact 0.14-0.37 mm ²	0.00061	Brass	Au	0.9	2.6	1
									1					Socket Contact 2.5 mm ²	0.00065	Brass	Ag/Cu	2.2	3.2	5
										1				Socket Contact 1.5 mm ²	0.00067	Brass	Ag/Cu	1.8	3.0	4
											1			Socket Contact 0.75-10 mm ²	0.00063	Brass	Ag/Cu	1.45	2.6	3
												1		Socket Contact 0.5 mm ²	0.00062	Brass	Ag/Cu	1.1	2.6	2
OBSOLETE														Socket Contact 0.14-0.37 mm ²	0.00061	Brass		0.9	2.6	1
OBSOLETE			1											Socket Contact 0.14-0.37 mm ²	0.00065	Fe	Au	0.9	2.6	1
												1		Socket Contact 0.14-0.37 mm ²	0.00067	Brass	Ag/Cu	0.9	2.6	1

[illegible]

HN.D-C-Bu.Ag/Ni:1,5 mm 2
HN.D-C-Bu.Ag/Ni:4,0 mm 2
HN.D-C-Bu-Cu/Ni:0,14 -0,37 mm 2
HN.D-C-Bu.Fe.Au:0,14 -0,37 mm 2
HN.D-C-Bu.Au:2,5 mm 2
HN.D-C-Bu.Au:1,5 mm 2
HN.D-C-Bu.Au:0,75-1,00 mm 2
HN.D-C-Bu.Au:0,5 mm 2
HN.D-C-Bu.Au:0,14 -0,37 mm 2
HN.D-C-Bu.Ag:2,5 mm 2
HN.D-C-Bu.Ag:1,5 mm 2
HN.D-C-Bu.Ag:0,75-1,00 mm 2
HN.D-C-Bu.Ag:0,5 mm 2
HN.D-C-Bu.Ag:0,14 -0,37 mm 2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 23.07.1997 Braun CHK 23.07.1997 Schnurpfeil		 TE Connectivity	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: ISO 2768 DIN 152 2768 mH-e DIN 9001-120		NAME SOCKET CONTACT SERIES HN.D -	
		APVD - PRODUCT SPEC 108-74018 APPLICATION SPEC 114-74015			
MATERIAL  -		FINISH  -		SIZE A2	CAGE CODE 00779
				DRAWING NO C=1105051	RESTRICTED TO -
CUSTOMER DRAWING				SCALE 10:1	SHEET 1 of 1
				REV B4	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1105051-2](#)