

LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN APVD
A1	-		C	CONTACT PIN MATERIAL AND PLATING CHANGE	18JUL2014	KJK JK



POS. PER ROW	L +0.3 -0.6	PART NUMBER	POS. PER ROW	L +0.3 -0.6	PART NUMBER
-	-	-	26	66.04	2-829 492-6
2	5.08	829 492-2	27	68.58	2-7
3	7.62	↑ -3	28	71.12	↑ 2-8
4	10.16	↑ -4	29	73.66	↑ 2-9
5	12.70	↑ -5	30	76.20	↑ 3-0
6	15.24	↑ -6	31	78.74	↑ 3-1
7	17.78	↑ -7	32	81.28	↑ 3-2
8	20.32	↑ -8	33	83.82	↑ 3-3
9	22.86	↑ -9	34	86.36	↑ 3-4
10	25.40	↑ -0	35	88.90	↑ 3-5
11	27.94	↑ -1	36	91.44	↑ 3-6
12	30.48	↑ -2	37	93.98	↑ 3-7
13	33.02	↑ -3	38	96.52	↑ 3-8
14	35.56	↑ -4	39	99.06	↑ 3-9
15	38.10	↑ -5	40	101.60	↑ 4-0
16	40.64	↑ -6	41	104.14	↑ 4-1
17	43.18	↑ -7	42	106.68	↑ 4-2
18	45.72	↑ -8	43	109.22	↑ 4-3
19	48.26	↑ -9	44	111.76	↑ 4-4
20	50.80	↑ -0	45	114.30	↑ 4-5
21	53.34	↑ -1	46	116.84	↑ 4-6
22	55.88	↑ -2	47	119.38	↑ 4-7
23	58.42	↑ -3	48	121.92	↑ 4-8
24	60.96	↑ -4	49	124.46	↑ 4-9
25	63.50	2-829 492-5	50	127.00	5-829 492-0

OBSELETE

OBSELETE



MATING SIDE: MIN. 0.7µm PdNi + MIN. 0.1µm GOLD FLASH BY AREA "F" OVER 1.27µm NICKEL
SOLDER SIDE: MIN. 3.0µm TIN OVER 1.27µm NICKEL




OBSELETE PARTS: OBSELETE CIS STREAMLINING PER D.RENAUD/D.SINISI



OBSELETE

1	CuZn	CONTACT PIN KONTAKTSTIFT
COLOUR BLACK	PCT	PIN HOUSING STIFTGEHAEUSE
REMARK BEMERKUNG	MATERIAL	DESCRIPTION BEZEICHNUNG



PC BOARD LAYOUT
LEITERPLATTEN-
ANSCHLUSSBILD

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN F.MUELLER 06NOV1989	TE TE Connectivity		
DIMENSIONS: mm		CHK M.SCHAARSCHMIDT 06NOV1989			
	TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.2mm		NAME AMPMODU II PIN HEADER TRIPLE ROW		
	0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ± FINISH ±		SIZE A3 CAGE CODE 00779 DRAWING NO C-829492 RESTRICTED TO -		
MATERIAL SEE TABLE		APVD -	WEIGHT -		
		PRODUCT SPEC 108-18012	CUSTOMER DRAWING		
		APPLICATION SPEC -	SCALE 5:1 SHEET 1 OF 1 REV C		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-829492-0](#)