

1/4" In-Line Stereo Jack 16PJ226-EX

KOBICONN





Dimensions: In.

| SPECIFICATIONS | |
|------------------------------------|-------------------------------------|
| Туре: | Stereo, 1/4", Open Circuit, In-Line |
| Breakdown Voltage: | 500VAC for 1 Minute |
| Contact Resistance: | 50Ω max. |
| Insulation Resistance: | 100MΩ @ 500VDC |
| Life Time: | 5,000 Cycles min. |
| Tolerance: | ± .012 inches |
| Cap: | ABS Resin |
| Terminal: | Nickel Plated Steel |
| Contact A: | Gold Plated PBS-EH, t=.03 |
| Contact B: | Nickel Plated PBS-EH, t=.03 |
| Body: | Polyphemeneoxide |
| Contact Spring: | Nickel Plated Piano Wire, ø0.4 |
| Metal Sleeve: | Nickel Plated Brass |
| RoHS Compliant by Exemption | |

Date Last Revised: 12-12-05

Available from Mouser Electronics 1-800-346-6873 www.mouser.com

16PJ226-EX

KC-300862

Specifications are subject to change without notice. No liability or warranty implied by this information. Environmental compliance based on producer documentation.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kobiconn: 16PJ226-EX