

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	4/0 STR/FLEX
Wire Type	Stranded Copper: Class B & C Compact, Class G, H, I, K, M, Locomotive
Wire Strip Length	2-5/16 in.
Stud Size	3/8 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	PURPLE
Panduit Die Index No. on Barrel	P54
Alternate Industry Die Index No. () on Barrel	(15)



Also stamped with:
4/0 STR/FLEX
LCBX4/0-38H

R.62 REF

1.19±.04

PANDUIT

.39±.04

.41±.02 DIA

Color coded barrel markings

PURPLE DIE P54 (15)

Beveled wire entry

.81±.01

.65±.01

2.24±.04

2.65 REF

45°±5°

3.12 REF

Wire inspection window

.16±.01

						 PANDUIT CORP. TINLEY PARK, ILLINOIS	
						LCBX4/0-38H-X Copper Lug - One-Hole, Long Flex Barrel, 45° Angle Tongue	
00	6/03	SAC	SAC	RELEASED	10850		
REV	DATE	BY	CHK	DESCRIPTION	ECN	SCALE N/A	DRAWING NO / CAD FILE LCBX4_0-38H-CUST

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[LCBX4/0-38H-X](#)