

	1	2	3	4
A	Empfohlener Ausschnitt fuer Rastbefestigung (Grat gegenueber Bestueckungsseite)		Wanddicke wall thickness	Ausschnittlaenge length of cut-out
	recommended cut-out for snap-in fixing (edge opposite to snap-in direction)		0.75 bis / to 1.25	19.2 -0.1
			1.25 bis / to 2	19.4 -0.1
	2 bis / to 3		19.8 -0.1	12.9 +0.1
B				
C				
D				
E	Aufschrift Marking Ⓜ 1801. 6(4)/250~5E4 10(4)/250~ T100/55 05 10A 125-250V AC 1/3HP 125V AC 1/2HP 250V AC R50			

Schliesser 1-polig
Fuer Geraete der Klasse II geeignet

SPNO
suitable for appliances of class II

VERTRAULICH-CONFIDENTIAL

© Alle Rechte bei Marquardt GmbH, auch fuer den Fall von Schutzrechtsanmeldungen. Jede Verfuegungsbefugnis, wie Kopier- und Weitergaberecht, bei uns.

© This document is the exclusive property of Marquardt GmbH. Without our consent, it may not be reproduced or given to third parties.

Fuer Form und Lage FOR SHAPE AND LOC.	☉ ≡	Allgemeintoleranzen UNTOLERANCED DIMENSIONS				Pause COPY	Blatt SHEET		Typ K	Zeichn./DRAWING NO. 1801.6222	Index
Fuer Winkel FOR ANGLE ± 2°		PROJECTION 	Abmasse und Nennmassbereiche Angaben in mm ALL DIMENSIONS ARE IN MILLIMETRES	Laengen LENGTH	Radien RADII	Original DIN A4 Massstab SCALE 1:1		Geraeteschalter Appliance Switch MARQUARDT Marquardt GmbH, D-78604 Rietheim-Weilheim			
			0-6 ± 0.2 >6-15 ± 0.4 >15-30 ± 0.4 >30-70 ± >70-120 ± >120-200 ±	± 0.2 ± ± ± ± ±	± 0.2 ± ± ± ± ±	0 10 20 30 mm					
c			g			CAD Medusa		Z		gepr./DRAWN BY 03.08.05 wj gepr./CHECKED BY mej Ersatz fuer/REPLACEMENT OF	
b			f			gepr./DRAWN BY 03.08.05 wj gepr./CHECKED BY mej		gepr./DRAWN BY 03.08.05 wj gepr./CHECKED BY mej			
a			e								
	43855	03.08.05 WJ	d			Ersatz fuer/REPLACEMENT OF		Z			
Ausg. ISSUE	Aenderung REVISION	gez. DRAWN BY	Ausg. ISSUE	Aenderung REVISION	gez. DRAWN BY						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Marquardt:](#)

[1801.6222](#)