

Specification Sheet

Part Number: TSRP2FW-6A



One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, Office White, 120ft/Carton

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 250-62600                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Type                | TSRP2-6A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Color               | Office White (OEWH)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Features & Benefits | <ul style="list-style-type: none"><li>• Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick re-entry as well as providing a secure installation of power cables.</li><li>• U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards.</li><li>• Manufactured from UL 94V-0 rated PVC material.</li><li>• Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.</li><li>• Large base for greater adhesive surface.</li><li>• Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface.</li><li>• Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking.</li><li>• Junction boxes can be used for electrical or data outlets.</li><li>• Designed to complement HellermannTyton's industry standard TSR low voltage raceway system.</li></ul> |

|                            |                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Quantity Per</b>        | carton                                                                                                                                                                                                                                                                                                                                                         |
| <b>Product Description</b> | HellermannTyton's TSRP power surface raceway is a one piece, non-metallic, adhesive backed latching raceway designed to aesthetically organize and route either power or communications cables. Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick reentry as well as providing a secure installation of power cables. |
| <b>Short Description</b>   | One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, Office White, 120ft/Carton                                                                                                                                                                                                                                                                            |
| <b>Global Part Name</b>    | TSRP2-6A-PVC-WH                                                                                                                                                                                                                                                                                                                                                |
| <b>Length L (Imperial)</b> | 6.0                                                                                                                                                                                                                                                                                                                                                            |
| <b>Length L (Metric)</b>   | 1.83                                                                                                                                                                                                                                                                                                                                                           |
| <b>Width W (Imperial)</b>  | 1.25                                                                                                                                                                                                                                                                                                                                                           |
| <b>Width W (Metric)</b>    | 31.75                                                                                                                                                                                                                                                                                                                                                          |
| <b>Height H (Imperial)</b> | .75                                                                                                                                                                                                                                                                                                                                                            |
| <b>Height H (Metric)</b>   | 19.05                                                                                                                                                                                                                                                                                                                                                          |
| <b>Material</b>            | Polyvinylchloride (PVC)                                                                                                                                                                                                                                                                                                                                        |
| <b>Material Shortcut</b>   | PVC                                                                                                                                                                                                                                                                                                                                                            |

|                                       |                |
|---------------------------------------|----------------|
| <b>Flammability</b>                   | UL 94 V0       |
| <b>Halogen free</b>                   | No             |
| <b>Operating Temperature (Metric)</b> | +122°F (+50°C) |
| <b>Reach Complaint(Article 33)</b>    | No             |
| <b>ROHS Complaint</b>                 | Yes            |
| <b>UL Listed (US and Canada)</b>      | Yes            |
| <b>UL Listed (US</b>                  | Yes            |
| <b>Package Quantity(Imperial)</b>     | 120            |
| <b>Package Quantity (Metric)</b>      | 36.58          |
| <b>Customs Number</b>                 | 3925900000     |