



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

|                                                |                                                                                                                                                |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                       | High Conductivity Seamless Copper Tube                                                                                                         |
| Plating                                        | Electro-Tin                                                                                                                                    |
| Wire Size & Type                               | Stranded Copper Flex Cable;<br>444.4 kcmil (1100/24) Diesel Locomotive, 400 kcmil Class K & Class M                                            |
| Wire Strip Length                              | 2-3/4 in.                                                                                                                                      |
| Stud Size                                      | 1/2 in.                                                                                                                                        |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90° C                                                                                                                                          |
| C.S.A Certified Wire Connector                 | Yes                                                                                                                                            |
| Panduit Color Code on Barrel                   | BROWN                                                                                                                                          |
| Panduit Die Index No. on Barrel                | P87                                                                                                                                            |
| Alternate Industry Die Index No. ( ) on Barrel | (20)                                                                                                                                           |



| 00  | 9/02 | SAB | DRL | RELEASED    | 10336 |
|-----|------|-----|-----|-------------|-------|
| REV | DATE | BY  | CHK | DESCRIPTION | ECN   |

**PANDUIT CORP. TINLEY PARK, ILLINOIS**

LCCF400-12-6  
Copper Lug - Two-Hole, Flared Long Barrel

SCALE  
N/A

DRAWING NO / CAD FILE

LCCF400-12-CUST

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[LCCF400-12-6](#)