

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION MAR .1992.
 © COPYRIGHT 1992 By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
J		P	LTR	DESCRIPTION	DATE	DWN	APVD
		G3		REVISED PER ECR-11-024209	30NOV11	H.U	N.Y

CIRCUIT NO. DATE CODE (HOT MARKING)

1 2 3 4 5 6 7 8 9 10

D/C

D-3500

AMP

52.8

27.18

3.8^{+0.6}/_{-0.4} (0.82) 5.08 ±0.4 7.62 ±0.4

9.6

3.34 ±0.4

45.72 ±0.05 (3.54) 5.08 ±0.05 1.1 ±0.1 穴 20箇所
 Ø1.1 ±0.1 20 PLC

5.08 ±0.05

Ø3 ±0.1 2 PLC
 3 ±0.1 穴 2箇所

ROUND Ø4 MIN 2 PLC
 ランド径最小4mm 2箇所

ヘッドハウジング外形
 リセプタクルハウジング外形

REFERENCE P.C. BOARD HOLE (NOT ACCUMULATE TOLERANCE)
 P.C. BOARD THICKNESS: 1.6 ±0.1
 基板厚: 1.6 ±0.1

参考基板取付け寸法(非累積公差)

45.72 ±0.3 5.08 ±0.3

1 2 3 4 5 6 7 8 9 10

18.17

1.5

6 ±0.4 5.08 ±0.3

5.08 ±0.4

リテンションレグ RETENTION LEG

CONTACT TAIL

45.72 ±0.4

1 材料; 熱可塑性ポリエステル樹脂(ガラス入り) 色; 黒	1 MATERIAL; GLASS FIELD THERMO PLASTIC, POLYESTER. COLOR; BLACK
2 製品規格; 108-5349	2 PRODUCT SPEC; 108-5349
3 製品認定報告書; 501-5013	3 QUALIFICATION TEST REPORT; 501-5013
△4 接触部仕上; ニッケル下地0.38 μMIN.金めっき	△4 FINISH (CONTACT AREA); 0.38u MIN. GOLD PLT. OVER NICKEL.
△5 接触部仕上; ニッケル下地0.76 μMIN.金めっき	△5 FINISH (CONTACT AREA); 0.76u MIN. GOLD PLT. OVER NICKEL.
△6 接触部仕上; ニッケル下地2.0 μMIN.すすめっき	△6 FINISH (CONTACT); 2.0u MIN. TIN PLT. OVER NICKEL.
△7 レグおよび脚部仕上; ニッケル下地半田めっき	△7 FINISH (RETENTION LEG AND CONTACT TAIL); TIN-LEAD-PLT. OVER NICKEL.
△8 6箇所マーキング、白	△8 6 PLACES MARKING, WHITE
△9 レグおよび脚部仕上; ニッケル下地すすめっき	△9 FINISH (RETENTION LEG AND CONTACT TAIL); TIN PLT. OVER NICKEL.
△10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI	

KEY LESS

1 2 3 4 5 6 7 8 9 10

△10 OBSOLETE	△9 △4	3-175365-2	△8
	△9 △6	175365-5	
	△9 △5	175365-3	
	△9 △4	175365-2	
FINISH	型番	PART NUMBER	マーキング

GENERAL TOLERANCE
一般公差

10 ≥ : ±0.2
 30 ≥ > 10: ±0.25
 100 ≥ > 30: ±0.3
 ANGLES: ±3°

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	18MAR1992	TE Connectivity	
		CHK	T.YONEBAYASHI		
DIMENSIONS: 単位: 耗 mm		APVD	07APR1992	NAME 名称	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差		PRODUCT SPEC	S.MANABE	DYNAMIC D-3500	
0 PLC ±-		APPLICATION SPEC	S.MANABE	20 POS HDR ASSY	
1 PLC ±-		取付適用規格		SIZE	CAGE CODE
2 PLC ±-		WEIGHT		A3	00779
3 PLC ±-		CUSTOMER DRAWING		DRAWING NO	番号
4 PLC ±-				C-175365	
ANGLES ±-				RESTRICTED TO	
FINISH 仕上				SCALE	SHEET
SEE NOTE 注記参照				2:1	1 of 1
				REV	G3

1470-19 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[175365-5](#)