


DB9 Male To DB9 Female, 6 Ft


9PAMF6



PRODUCT FEATURES

- Fully molded backshell with strain relief for added protection
- 28 AWG stranded conductors for flexibility
- Thumbscrews for tool-less termination

MECHANICAL DIAGRAM



P1	1006	P2
1	1	BROWN
2	2	RED
3	3	ORANGE
4	4	YELLOW
5	5	GREEN
6	6	BLUE
7	7	PURPLE
8	8	GREY
9	9	BLACK
SHIELD		SHIELD

*NOTE: All relevant materials are complied with RoHS directive

5	BLACK PVC TUBE $\phi 3.0 \times 22\text{mm}$
	ALUMINUM FOIL $33 \times 65\text{mm}$
	MOLDED PE COLOR TRANSPARENT
	MOLDED PVC BEIGE
4	NON-UL 9C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BEIGE, DRAWING NO. EMAL2809C-051
3	MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BEIGE
2	DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR
1	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR

9PAMF6_R1_4715ds

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[B+B SmartWorx:](#)

[9PAMF6](#)