

4		3		2		1	
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION			
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.				LOC GP DIST 00			
Tooling Drawing NO.				P LTR		REVISIONS	
USB A: TR00662				C		DESCRIPTION	
						DATE	
						DWN	
						APVD	
						REVISE PER ECO-05-006320	
						01AUG05	
						TW	
						JH	
<div><div><div>Pos.4</div><div>Pos.1</div></div><div><div>1</div><div>3</div><div>5</div><div>4</div><div>2</div></div><div><div>25±5</div><div>1000⁺⁰₋₅₀</div></div></div> <div><div>TYCO P/N</div><div>T/D YYWW</div><div>MADE IN CHINA</div></div> <div><div>(25)</div><div>(13)</div><div>(35)</div></div> <div>LABEL</div>							

PIN ASSIGNMENT :

USB A

2

3

1

4

Shell

Pair 1

White(D-)

Green(D+)

Red(Vbus)

Black(Gnd)

Drain

Braid

NC

NC

NC

NC

NC

NOTES:

1. TESTED FOR CONTINUITY, SHORTS AND OPENS, HI-POT 630V FOR 10MS.

2. CABLE ASSEMBLY MEETS USB 2.0 STANDARDS.

3. EXPOSED CABLE BRAID IS NOT PERMISSIBLE BEYOND OVERMOLD.

4. THE FINAL CABLE ASSEMBLY MAXIMUM LENGTH NOT TO EXCEED 1700MM PER USB SPECIFICATIONS.

5. MEETS REQUIREMENTS OF EU DIRECTIVE 2002/95/EC

AR	MR	COPPER FOIL, W: 5MM	5
1	PC	LABEL, 25x35mm, White 25x13mm	4
AR	KG	Overmold PVC, 40P, Color: White(WH01)	3
AR	MR	USB 2.0 Cable 28AWG*1P+26AWG*2C+Al/Mylar +Drain+Braid, Color: White(WH01).	2
1	PC	USB 4Pin Connector Contacts: Gold 30U Plated, Shell: Nickel Plated, Housing UL94V-0 A Type.	1
-1	U/M	DESCRIPTION	ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN BOVEY LIU 25FEB02	Tyco Electronics Corporation	
CHK J.HUNT 25FEB02		Harrisburg, Pa 17105-3608		
APVD J.HUNT 25FEB02		NAME		
PRODUCT SPEC		CABLE ASSEMBLY, USB A TYPE TO NC		
APPLICATION SPEC				
WEIGHT		SIZE A3	CAGE CODE 00779	
CUSTOMER DRAWING		DRAWING NO C-1487592		
		SCALE N.T.S	SHEET 1 OF 1	
		REV C		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1487592-1](#)