



Product: <u>9888</u> ☑

50 Ohm Triax RG-8/U Type, 11 AWG BC, FPO, BC Braids, PE Jkt

Product Description

50 Ohm Triax RG-8/U Type, 11 AWG stranded (7x19) .108" bare copper conductor, foam polyethylene insulation, double bare copper braid shield (95% & 80% coverage) polyethylene jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material Nominal Diameter No. of Coax 11 7x19 BC - Bare Copper 0.108 in 1 Conductor Count: 1

Insulation

Material	Nominal Diameter
PE - Polyethylene (Foam)	0.285 in

Inner Shield Material

Type	Material	Coverage [%]
Braid	BC - Bare Copper	96 %

Inner Jacket Material

Material	Nominal Diameter
PE - Polyethylene	0.37 in

Outer Shield Material

Type	Material	Coverage [%]
Braid	BC - Bare Copper	95 %
Braid	BC - Bare Copper	80 %

Outer Jacket Material


Material	Nominal Diameter	No	ominal Wall Thickness
PE - Polyethylene	0.48 in	0.0	04 in
Weight:	Veight:		0.261 lbs

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Inner Shield DCR	Nominal Outer Shield DCR
1.2 Ohm/1000ft	1.2 Ohm/1000ft	2.1 Ohm/1000ft

Capacitance



Inductance

Nominal Inductance

Impedance

Nominal Characteristic Impedance
50 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.1 dB/100ft
10 MHz	0.5 dB/100ft
50 MHz	1.2 dB/100ft
100 MHz	1.8 dB/100ft
200 MHz	2.7 dB/100ft
400 MHz	4.2 dB/100ft
700 MHz	5.8 dB/100ft
900 MHz	6.7 dB/100ft
1000 MHz	7.1 dB/100ft

Delay

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
78 ns/100m	1.3 ns/ft	78 %

Voltage

Non-UL Voltage Rating
300 (Between shield) V RMS

Temperature Range

Non-UL Temp Rating:	80°C
Operating Temp Range:	-55°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	130 lbs/1000ft
Max Recommended Pulling Tension:	326 lbs
Min Bend Radius/Minor Axis:	5 in

Standards

RG Type:	8/U Type

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
, ,	

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
9888 010500	Black	Reel	500 ft	612825260035
9888 0101000	Black	Reel	1,000 ft	612825260028

Footnote: C - CRATE REEL PUT-UP.

History

Update and Revision: Revision Number: 0.263 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 9888 0101000 9888 010500