

# Null Modem Serial DB9 Serial Cable (DB9 to DB25 F/M), 6 ft.

MODEL NUMBER: P456-006







### Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 6ft cable has a DB9 female connector on one end and a DB25 male connector on the other. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

#### **Features**

- DB9 female to DB25 male
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity

# **Highlights**

- Superior molded cables with foilshielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

## **System Requirements**

 Two serial devices (one with a DB25 Male connector and the Other with a DB9 Female connector) requiring a null modem (cross-wired) configuration.

### **Package Includes**

 6-ft. Null Modem Gold Cable DB9F to DB25M

# **Specifications**

| OVERVIEW                        |                      |  |
|---------------------------------|----------------------|--|
| UPC Code                        | 037332013354         |  |
| INPUT                           |                      |  |
| Cable Length (ft.)              | 6                    |  |
| Cable Length (m)                | 1.8                  |  |
| PHYSICAL                        |                      |  |
| Color                           | Black                |  |
| Shipping Dimensions (hwd / cm)  | 21.59 x 17.53 x 1.27 |  |
| Shipping Dimensions (hwd / in.) | 8.50 x 6.90 x 0.50   |  |



**Tripp Lite**1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

|  | •                                 |  |
|--|-----------------------------------|--|
| Shipping Weight (kg)                   | 0.17                              |  |
| Shipping Weight (lbs.)                 | 0.37                              |  |
|  |                                   |  |
| CONNECTIONS                            |                                   |  |
| Side A - Connector 1                   | DB9 (FEMALE)                      |  |
| Side B - Connector 1                   | DB25 (MALE)                       |  |
|  |                                   |  |
| FEATURES & SPECIFICATIONS              |                                   |  |
| Technology                             | Modem; Null Modem; Serial (RS232) |  |
|  |                                   |  |
| WARRANTY                               |                                   |  |
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty         |  |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>