


REV. 0  
DCO 143373

|                 |                            |
|-----------------|----------------------------|
| COIL: @ 25°C    |                            |
| RESISTANCE      | 3300 OHMS ±10%             |
| NOMINAL VOLTAGE | 26.5 VDC                   |
| MUST OPERATE    | 15.2 VDC                   |
| MUST RELEASE    | 10.8 VDC MAX; 1.7 VDC MIN. |

|              |                           |
|--------------|---------------------------|
| ENVIRONMENT: |                           |
| VIBRATION    | 10 Hz TO 3000 Hz @ 30 g's |
| SHOCK        | 75 g's 6 MS. DURATION     |
| TEMPERATURE  | -65 °C TO +125 °C         |

NOTES: OPERATE TIME 4.0 MS MAX.  
RELEASE TIME 7.5 MS MAX.  
CONTACT STABILIZATION TIME 2.0 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1A  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. ASB 12/19/01 *CK* 12/19/01



CUST. GPL  
CUST. NO. M39016/21-038P REV.

"JMSDD" RELAY

JMSCDD-26XP

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMSCDD-26XP](#)