
XZCP1440L5

pre-wired connectors XZ - elbowed female - M12 - 3 pins - cable PUR 5m

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	General purpose
Electrical connection	Elbowed female connector M12, 3 pins
Collar material	Metal
Status LED	2 NPN LEDs
Cable length	16.4 ft (5 m)

Complementary

Cable connector fixing	Screw-on	
Cable outer diameter	0.2 in (5.2 mm)	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	1030 V DC	
[In] rated current	4 A	
Contact resistance	<= 5000 μOhm	
Insulating resistance	>= 1 GΩ	
Product weight	0.4 lb(US) (0.18 kg)	

Environment

IP degree of protection	IP67	
Ambient air temperature for operation	23176 °F (-580 °C) (flexing) -40176 °F (-4080 °C) (static)	
Ambient air temperature for storage	-40176 °F (-4080 °C)	

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389110763294
Nbr. of units in pkg.	1
Package weight(Lbs)	0.41
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	PL

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0726 - Schneider Electric declaration of conformity

Contractual warranty

Contracted Warranty		
Period	18 months	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCP1440L5