



PART NUMBER

LCD-S301C31TR-3

REV.

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	E.C.N. #11244.	5.17.05
В	E,C,N, #11148.	02.08.07





PIN NO.	1	2	3	4	5	6	7	8
SEGMENT	COM	E1	D1	C1	DP1	E2	D2	C2
PIN NO.	3	10	11	12	13	14	15	16
SEGMENT	DP2	E3	D3	끙	B3	A3	F3	G3
PIN NO.	17	18	19	20	21	22	23	24
SEGMENT	B2	A2	F2	ઉ	B1	A 1	F1	G1

CHARACTERISTICS					
FLUID TYPE:	TN				
BACKGROUND COLOR:	GRAY				
VIEWING DIRECTION:	6:00				
DISPLAY MODE:	REFLECTIVE				
OPERATING VOLTAGE:	3.0 VAC				
OPERATING TEMP.	O'C TO 50'C				
STORAGE TEMP.	-20°C TO 70°C				
DRIVING METHODE;	STATIC				
CONNECTION TYPE:	24 PINS				

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN= +DECINAL PRECISION MAX. = +0.00 —DECINAL PRECISION

B LCD-S301C31TR-3

0.31" CHARACTER HEIGHT, THREE DIGIT LCD GLASS,
TN, REFLECTIVE, 24 PINS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX NO. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLISSINE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FALURE.

PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067–6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com

US WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 6.30.03
PAGE: 1 OF 1
JC
SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

LCD-S301C31TR-3