

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0014441612

Status:


Active

Overview:

SL Modular Connectors

Description:

2.54mm Pitch SL Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26 AWG, 0.38µm Gold (Au), 12 Circuits



|                                                          |                                                                 |
|----------------------------------------------------------|-----------------------------------------------------------------|
| Documents:                                               |                                                                 |
| <a href="#">3D Model</a>                                 | <a href="#">Product Specification TS-70541-001-001 (PDF)</a>    |
| <a href="#">Drawing (PDF)</a>                            | <a href="#">Packaging Specification PK-70873-0001-001 (PDF)</a> |
| <a href="#">Product Specification PS-70400-001 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>            |

|                                |                                     |
|--------------------------------|-------------------------------------|
| Agency Certification           |                                     |
| CSA                            | LR19980                             |
| UL                             | E29179                              |
| General                        |                                     |
| Product Family                 | Ribbon Cable / Wire Trap Connectors |
| Series                         | 70475                               |
| Comments                       | Terminals Preloaded                 |
| Component Type                 | Housing                             |
| Glow-Wire Capable              | No                                  |
| Overview                       | SL Modular Connectors               |
| Product Name                   | SL                                  |
| UPC                            | 800753981560                        |
| Physical                       |                                     |
| Circuits (Loaded)              | 12                                  |
| Circuits (maximum)             | 12                                  |
| Color - Resin                  | Black                               |
| Durability (mating cycles max) | 50                                  |
| Entry Angle                    | Vertical                            |
| Flammability                   | 94V-0                               |
| Lock to Mating Part            | None                                |
| Material - Metal               | Phosphor Bronze                     |
| Material - Plating Mating      | Gold                                |
| Material - Plating Termination | Tin                                 |
| Material - Resin               | Polyester Alloy                     |
| Number of Rows                 | 1                                   |
| PCB Retention                  | None                                |
| Packaging Type                 | Tube                                |
| Pitch - Mating Interface       | 2.54mm                              |
| Polarized to Mating Part       | No                                  |
| Stackable                      | Yes                                 |
| Surface Mount Compatible (SMC) | N/A                                 |
| Temperature Range - Operating  | -40° to +105°C                      |
| Termination Interface: Style   | IDT or Pierce                       |
| Wire Insulation Diameter       | 1.35mm max.                         |
| Wire Size AWG                  | 26                                  |
| Wire/Cable Type                | Discrete Wire, Ribbon Cable         |
| Electrical                     |                                     |
| Current - Maximum per Contact  | 1.8A                                |
| Voltage - Maximum              | 250V                                |
| Material Info                  |                                     |
| Engineering Number             | 70475-0781                          |
| Reference - Drawing Numbers    |                                     |

EU ELV

Not Reviewed

EU RoHS

China RoHS

Not Reviewed

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

Need more information on product environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

|                 |              |
|-----------------|--------------|
| China ROHS      | Not Reviewed |
| ELV             | Not Reviewed |
| RoHS Phthalates | Not Reviewed |

Search Parts in this Series

70475 Series

Mates With

70004 Interim Clip (Single Row), 70013 Interim Clip (Dual Row)

Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG

Packaging Specification  
Product Specification  
Sales Drawing

PK-70873-0001-001  
PS-70400-001, TS-70541-001-001  
SDA-70475-0771-0794

This document was generated on 08/23/2018

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

14-44-1612