

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

By

ALL RIGHTS RESERVED.

LOC

DIST

REV

PER

ECO

15-005911

DATE

5-28-15

DWN

CT

APVD

DM

1. THIS CONNECTOR ASSEMBLY IS SUPPLIED WITH METAL CONTACT RETENTION CLIPS INSTALLED IN THE INSERT ASSEMBLY.

2. THIS CONNECTOR ASSEMBLY MEETS THE REQUIREMENTS OF LORAL SPEC 010772 AND MATES WITH ANY PLUG CONNECTOR WITH SAME INSERT ARRANGEMENT.

3. MARK WITH .047 [1.19]—.062 [1.57] HIGH CHARACTERS. FAR SIDE REFERS TO THE WIDE SIDE OF THE KEYSTONE. NEAR SIDE REFERS TO THE NARROW SIDE OF THE KEYSTONE. IF THE REAR SHELL IS TOO SMALL FOR THE ENTIRE CUSTOMER PART NUMBER, MARKING SHALL BE LOCATED AS FOLLOWS:

A. CUSTOMER BASE NUMBER, ON FRONT SHELL, FAR SIDE.

B. CUSTOMER DASH NUMBER ON REAR SHELL, FAR SIDE.

C. "AMP" AND DATE CODE ON FRONT SHELL, NEAR SIDE.

D. AMP PART NUMBER ON REAR SHELL, NEAR SIDE.

4. POINT OF ELECTRICAL ENGAGEMENT — AS MEASURED WITH A .039 [0.99] — .041 [1.04] DIAMETER SQUARE ENDED TEST PIN. CONTACT SHOWN INSTALLED FOR DIMENSIONAL REFERENCE ONLY.

5. MAXIMUM WIRE INSULATION TO BE USED WITH THIS CONNECTOR ASSEMBLY IS .072 [1.83] DIAMETER.

6. FOR CONTACT CRIMPING INSTRUCTION SHEET REFER TO AMP IS 7516. FOR CONTACT INSTALLATION AND REMOVAL INSTRUCTION SHEET REFER TO AMP IS 7508.

8. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M—1982.

9. THIS DRAWING SHALL BE INTERPRETED IN ACCORDANCE WITH APPLICABLE STANDARDS LISTED IN MIL—STD—100.

PRELIMINARY—NOT RELEASED FOR PRODUCTION	.040 .020 [1.02 0.51]	.432 .412 [10.97 10.46]	1.093 1.073 [27.76 27.25]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	1.317 1.307 [33.45 33.20]	.976 .966 [24.79 24.54]	1.556 1.526 [39.52 38.76]	MS18274—1	15	2	B010772—0043	3—448816—2	3—448816—2
PRELIMINARY—NOT RELEASED FOR PRODUCTION	.049 .029 [1.24 0.74]	.544 .524 [13.82 13.31]	2.188 2.168 [55.58 55.07]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.620 .590 [15.75 14.99]	.428 .418 [10.87 10.62]	2.411 2.401 [61.24 60.99]	2.069 2.059 [52.55 52.30]	2.650 2.620 [67.31 66.55]	MS18277—1	50	5	B010772—0032	1—448816—5	1—448816—5
			2.282 2.262 [57.96 57.45]					2.505 2.495 [63.63 63.37]	2.164 2.154 [54.97 54.71]	2.744 2.714 [69.70 68.94]	MS18276—1	37	4	B010772—0030	1—448816—4	1—448816—4
PRELIMINARY—NOT RELEASED FOR PRODUCTION	.040 .020 [1.02 0.51]	.432 .412 [10.97 10.46]	1.635 1.615 [41.53 41.02]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	1.857 1.847 [47.17 46.91]	1.516 1.506 [38.51 38.25]	2.103 2.073 [53.42 52.65]	MS18275—1	25	3	B010772—0028	1—448816—3	1—448816—3
			1.093 1.073 [27.76 27.25]					1.317 1.307 [33.45 33.20]	.976 .966 [24.79 24.54]	1.556 1.526 [39.52 38.76]	MS18274—1	15	2	B010772—0026	1—448816—2	1—448816—2
PRELIMINARY—NOT RELEASED FOR PRODUCTION	.040 .020 [1.02 0.51]		.769 .749 [19.53 19.02]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	.989 .979 [25.12 24.87]	.648 .638 [16.46 16.21]	1.228 1.198 [31.19 30.43]	MS18273—1	9	1	B010772—0024	1—448816—1	1—448816—1
		.544 .524 [13.82 13.31]	2.188 2.168 [55.58 55.07]					2.411 2.401 [61.24 60.99]	2.069 2.059 [52.55 52.30]	2.650 2.620 [67.31 66.55]	MS18277—1	50	5	A010772—0010	1—448816—0	1—448816—0
	.049 .029 [1.24 0.74]		2.282 2.262 [57.96 57.45]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	2.505 2.495 [63.63 63.37]	2.164 2.154 [54.97 54.71]	2.744 2.714 [69.70 68.94]	MS18276—1	37	4	A010772—0008	448816—9	448816—9
		.432 .412 [10.97 10.46]	1.635 1.615 [41.53 41.02]					1.857 1.847 [47.17 46.91]	1.516 1.506 [38.51 38.25]	2.103 2.073 [53.42 52.65]	MS18275—1	25	3	A010772—0006	448816—8	448816—8
	.040 .020 [1.02 0.51]		1.093 1.073 [27.76 27.25]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	1.317 1.307 [33.45 33.20]	.976 .966 [24.79 24.54]	1.556 1.526 [39.52 38.76]	MS18274—1	15	2	A010772—0004	448816—7	448816—7
			.769 .749 [19.53 19.02]					.989 .979 [25.12 24.87]	.648 .638 [16.46 16.21]	1.228 1.198 [31.19 30.43]	MS18273—1	9	1	A010772—0002	448816—6	448816—6
	.049 .029 [1.24 0.74]	.544 .524 [13.82 13.31]	2.188 2.168 [55.58 55.07]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	2.411 2.401 [61.24 60.99]	2.069 2.059 [52.55 52.30]	2.650 2.620 [67.31 66.55]	MS18277—1	50	5	B010772—0010	448816—5	448816—5
			2.282 2.262 [57.96 57.45]					2.505 2.495 [63.63 63.37]	2.164 2.154 [54.97 54.71]	2.744 2.714 [69.70 68.94]	MS18276—1	37	4	B010772—0008	448816—4	448816—4
	.040 .020 [1.02 0.51]	.432 .412 [10.97 10.46]	1.635 1.615 [41.53 41.02]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	1.857 1.847 [47.17 46.91]	1.516 1.506 [38.51 38.25]	2.103 2.073 [53.42 52.65]	MS18275—1	25	3	B010772—0006	448816—3	448816—3
			1.093 1.073 [27.76 27.25]					1.317 1.307 [33.45 33.20]	.976 .966 [24.79 24.54]	1.556 1.526 [39.52 38.76]	MS18274—1	15	2	B010772—0004	448816—2	448816—2
	.040 .020 [1.02 0.51]		.769 .749 [19.53 19.02]	.248 .238 [6.30 6.05]	.439 .419 [11.15 10.64]	.509 .479 [12.93 12.17]	.316 .306 [8.03 7.77]	.989 .979 [25.12 24.87]	.648 .638 [16.46 16.21]	1.228 1.198 [31.19 30.43]	MS18273—1	9	1	B010772—0002	448816—1	448816—1
L		J	H			E	D	C	B	A	INSERT ARRANGEMENT	NO OF POS	SHELL SIZE	CUSTOMER P/N ON CONNECTOR	AMP P/N ON CONNECTOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES

MATERIAL
SEE CALLOUTS

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ± .
1 PLC ± .
2 PLC ± .
3 PLC ± .
4 PLC ± .

ANGLES
± ° 1'

FINISH
SEE CALLOUTS

DWN
A.J. GRAFF
2-11-93

CHK
F. KINSEY
2-17-93

APVD
F. KINSEY
2-17-93

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

NAME

AMPLIMITE NONMAGNETIC RECEPTACLE ASSY
WITH SIZE 20 CRIMP TYPE SOCKET CONTACTS
SERIES 109, SHELL SIZES 1 THRU 5

SIZE
A1

CAGE CODE
00779

DRAWING NO
448816

RESTRICTED TO

SCALE
4:1

SHEET
1




OF
2

REV
E

TE Connectivity

4805 (3/11)

LOC		DIST		REVISIONS			
P	L	T	R	DESCRIPTION	DATE	DWN	APVD
—	—	—	—	SEE SHEET 1	—	—	—



CONTACT
AMP P/N 206793-1 (AWG 20-24)
OR 206795-1 (AWG 26-28)

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A.J. GRAFF 2-11-93	TE Connectivity	
		CHK F. KINSEY 2-17-93		
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME
		0 PLC	± .-	PRODUCT SPEC
		1 PLC	± .-	MIL-C-24308
		2 PLC	± .-	APPLICATION SPEC
		3 PLC	± .-	
		4 PLC	± .-	SIZE
		ANGLES	± .-	CAGE CODE
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS	WEIGHT	DRAWING NO
			—	A100779
				448816
				RESTRICTED TO
				—
				CUSTOMER DRAWING
				SCALE 4:1
				SHEET 2 OF 2
				REV E

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-448816-4](#)