

HSEC8-149-01-L-DV-A



HSEC8-DV SERIES

(0.80 mm) .0315"

VERTICAL EDGE RATE® CARD SOCKET

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com/HSEC8-DV

Insulator Material:

Black Liquid Crystal Polymer

Contact:

BeCu

Plating:

Au or Sn over

50 μ" (1.27 μm) Ni

Current Rating:

2.8 A per pin
(2 adjacent pins powered)

Operating Temp:

-55 °C to +125 °C

RoHS Compliant:

Yes

Card Mates:


(1.60 mm) .062" card,
(2.36 mm) .093" card,
HSC8

Cable Mates:


ECDP



Mates with (1.60 mm) .062"
or (2.36 mm) .093" cards



MISALIGNMENT MITIGATION



Custom designs compensate for misalignment.

PROCESSING

Lead-Free Solderable:

Yes

SMT Lead Coplanarity:

(0.10 mm) .004" max (10-60)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



FILE NO. E111594

HIGH-SPEED CHANNEL PERFORMANCE

HSEC8-DV

Rating based on Samtec reference channel.
For full SI performance data visit Samtec.com
or contact SIG@samtec.com

28
Gbps

HSEC8 - 1 POSITIONS PER ROW - CARD THICKNESS - PLATING OPTION - DV - A - OTHER OPTION

09, 10, 13, 20,
25, 30, 37, 40, 49,
50, 60, 70, 80, 100
(13, 25, 49 only available
with -L or -L2 option;
09 only available with -L2 option;
37 only available with -L option)

-01
= (1.60 mm) .062"
thick card

-03
= (2.36 mm) .093"
thick card

-L
= 10 μ" (0.25 μm) Gold on contact,
Matte Tin on tail

-S
= 30 μ" (0.76 μm) Gold on contact,
Matte Tin on tail

-K
= (7.01 mm) .276" DIA
Polyimide Film
Pick & Place Pad
(with -01 card)
= (6.25 mm) .246" DIA
Polyimide Film
Pick & Place Pad
(with -03 card)



-BL
= Board Locks
(-01 card only)
(Weld tab standard)

-L
= Latching Option
(-01 card only)
(13, 25, 37, 49 only)
(Weld tab standard)


-L2
= ECDP Latching
(-01 card only)
(09, 13, 25, 49 only)
(For use with ECDP)
(Weld tab standard)

-WT
= Weld tab

-TR
= Tape & Reel
(09 - 70 only)



09, 13, 25, 37, 100



CABLE	CONNECTOR
ECDP-04	HSEC8-109-L2
ECDP-08	HSEC8-113-L2
ECDP-16	HSEC8-125-L2
ECDP-32	HSEC8-149-L2

Notes:

While optimized for 50 Ω applications, this connector with alternative signal/ground patterns may also perform well in certain 75 Ω applications.

Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications.

Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

[HSEC8-113-01-L-DV-A-K-TR](#) [HSEC8-149-01-L-DV-A-K](#) [HSEC8-160-01-L-DV-A-WT](#) [HSEC8-113-01-S-D-EM2](#)
[HSEC8-190-01-L-DV-A-WT](#) [HSEC8-109-01-S-RA-L2](#) [HSEC8-149-01-S-DV-A-K-TR](#) [HSEC8-1100-01-SM-DV-A](#)
[HSEC8-125-01-SM-DV-A-WT-K](#) [HSEC8-120-01-S-DV-A-PE-K-TR](#) [HSEC8-113-01-L-RA-L2-TR](#) [HSEC8-1100-01-S-DV-](#)
[A-BL-K](#) [HSEC8-190-03-L-DV-A-K](#) [HSEC8-113-01-L-DV-A-PE-K-TR](#) [HSEC8-130-01-L-PV-2-1](#) [HSEC8-113-01-L-RA](#)
[HSEC8-120-01-L-RA-TR](#) [HSEC8-140-01-SM-DV-A-WT](#) [HSEC8-160-03-S-DV-A](#) [HSEC8-137-01-S-D-EM2](#) [HSEC8-](#)
[140-01-L-PV-4-2](#) [HSEC8-140-03-S-DV-A](#) [HSEC8-149-01-S-DV-A-L](#) [HSEC8-113-01-H-DV-A-PE-TR](#) [HSEC8-140-01-](#)
[SM-DV-A-K-TR](#) [HSEC8-130-01-S-DV-A-WT-K](#) [HSEC8-110-01-L-DV](#) [HSEC8-120-01-H-DV-A-K-TR](#) [HSEC8-125-01-L-](#)
[DV-A-L2-K](#) [HSEC8-120-01-L-PV-4-1](#) [HSEC8-110-01-L-DV-A-WT-K-TR](#) [HSEC8-109-01-L-DV-A-L2-K](#) [HSEC8-150-01-](#)
[S-DV-A-TR](#) [HSEC8-130-01-S-DV-A-WT](#) [HSEC8-130-01-L-PV-4-1](#) [HSEC8-125-01-L-DV-A-WT](#) [HSEC8-137-01-L-DV-](#)
[A-K-TR](#) [HSEC8-137-01-S-DV-A](#) [HSEC8-125-01-S-DV-A-L2-K](#) [HSEC8-110-01-L-DV-A-GR-K-TR](#) [HSEC8-110-03-S-](#)
[DV-A](#) [HSEC8-120-01-S-DV-A-WT-K-TR](#) [HSEC8-113-01-S-RA-L2](#) [HSEC8-160-01-SM-DV-A-BL-K](#) [HSEC8-170-01-S-](#)
[DV-A-BL-K](#) [HSEC8-130-01-S-PV-4-2](#) [HSEC8-190-01-L-DV-A-BL-K](#) [HSEC8-160-01-L-DV-A-K](#) [HSEC8-113-01-S-DV-](#)
[A-PE-K-TR](#) [HSEC8-125-01-S-DV-A-K](#) [HSEC8-150-01-SM-DV-A-K](#) [HSEC8-140-01-SM-DV-A-BL-K](#) [HSEC8-125-01-L-](#)
[DV-A-WT-K-TR](#) [HSEC8-190-01-S-DV-A-WT-K](#) [HSEC8-113-01-SM-DV-A-L2-K-TR](#) [HSEC8-120-01-L-DV-A-PE-K](#)
[HSEC8-130-01-L-DV-A-WT-K-TR](#) [HSEC8-160-03-L-DV-A-WT](#) [HSEC8-125-01-L-DV-A-L](#) [HSEC8-130-03-S-DV-A-K](#)
[HSEC8-170-01-S-DV-A-WT-K-TR](#) [HSEC8-113-01-SM-DV-A](#) [HSEC8-190-01-L-DV-A](#) [HSEC8-180-01-S-DV-A-BL-K](#)
[HSEC8-1100-01-S-DV-A-WT](#) [HSEC8-125-01-SM-DV-A](#) [HSEC8-160-01-S-DV-A-GR-TR](#) [HSEC8-125-01-L-RA-TR](#)
[HSEC8-170-01-SM-DV-A](#) [HSEC8-110-01-SM-DV-A-PE-K-TR](#) [HSEC8-113-01-S-DV-L2](#) [HSEC8-120-01-S-DV-A-GR-K-](#)
[TR](#) [HSEC8-160-01-S-DV-K](#) [HSEC8-120-01-L-DV-A-BL-K-TR](#) [HSEC8-120-01-S-DV-A-WT](#) [HSEC8-109-01-S-DV-A-WT](#)
[HSEC8-160-01-S-DV](#) [HSEC8-150-01-S-DV-A-GR-K-TR](#) [HSEC8-150-03-S-DV-A](#) [HSEC8-150-01-L-DV-A-BL](#) [HSEC8-](#)
[1100-03-L-DV-A](#) [HSEC8-150-01-H-DV-A](#) [HSEC8-149-01-L-RA-L2-TR](#) [HSEC8-120-03-H-DV-A](#) [HSEC8-113-01-L-DV-](#)
[A-L2-K](#) [HSEC8-137-01-S-DV-L-A](#) [HSEC8-160-01-SM-DV-A-BL](#) [HSEC8-130-01-L-PV-4-1-WT](#) [HSEC8-130-01-S-PV-2-](#)
[1-WT](#) [HSEC8-170-01-L-DV-A-WT-K-TR](#) [HSEC8-110-01-SM-DV-A-TR](#) [HSEC8-110-01-S-DV-A-WT-K](#) [HSEC8-150-01-](#)
[L-DV-A-TR](#) [HSEC8-120-01-L-DV-A-WT](#) [HSEC8-125-01-H-DV-A](#) [HSEC8-160-01-L-DV-A-TR](#) [HSEC8-160-01-SM-DV-](#)
[A-BL-K-TR](#) [HSEC8-140-01-SM-DV-A-BL](#) [HSEC8-137-01-S-D-EM2L](#) [HSEC8-149-01-L-D-EM2](#)