



## **SUMMARY**

#### # Wires



Image is for illustrative purpose only

Series 2B

Termination type No contacts / Accessory

IP rating (

AWG wire size 0.00 - 0.00

Cable Ø 4.50 - 5.00 mm

**Status** active

### **Download**

Request a quote

Catalog

### **TECHNICAL DETAILS**

### **Mechanics**

Shell Style/Model GMA\*: Bend relief Grey

**Keying** No keying

Housing Material Silicone elastomer VMQ

**Variant** G: Gray

Weight 1.65 g

### **Performance**

Configuration

Insulator G: PEEK/Pehd

**Rated Current** 

### **Others**


Temp (min / max):  $-60^{\circ}$ C /  $+200^{\circ}$ C

Temperature range in water steam: +140°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **DRAWINGS**

### **Draws**



No keying

### **Dimensions**

	Α	L
mm.	4.5	41
in.	0,18	1,61

# **RECOMMENDED BY LEMO**

### **Tools**

### **Cables**

120222		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.