



## 2.75W Compact Fixed Blade Charger Small/Thin Wall Plug Adapter with DC Cord



### Features

- North America Fixed Blade AC Input
- CC & CV control
- Level VI Efficiency
- Class 2 Output per UL 1310
- Limited Power Source
- Class B EMI
- No Y Caps
- Standard Barrel Connector or Micro-B

### Applications

- MPEG Players
- PDAs
- Medical Test Device Charging
- Personal Electronics
- Digital Cameras
- Cordless Tools

### Safety Approvals

- cUL/UL
- Class 2 Output per UL 1310

### Mechanical Characteristics

- Length: 39.4mm (1.65in)
- Width: 43mm (1.65in)
- Height: 21.0mm (0.87in)
- Weight: 45g (1.59oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple P-P (max)	Regulation	
		Min.	Max.		Line	Load
PSM03A-050	5V	0A	0.55A	100mV	±5%	
PSM03A-050(M) <sup>(1)</sup>	5V	0A	0.55A	100mV	±5%	
PSM03A-075	7.5V	0A	0.366A	100mV	±5%	
PSM03A-090	9V	0A	0.305A	100mV	±5%	
PSM03A-120	12V	0A	0.23A	200mV	±5%	

Note (1): This unit is terminated with Micro-B connector in place of standard DC Cable.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phihong:](#)

[PSM03A-050-R](#) [PSM03A-075-R](#) [PSM03A-120-R](#) [PSM03A-100-R](#) [PSM03A-090-R](#) [PSM03A-050\(M\)](#)